

Badger Mechanical Heat Detector Links

Thermo Bulb Detector Link Ratings

Standard Response (BTBS) Part # (5-Pack)	Rapid Response (BTBR) Part # (5-Pack)	Detector Temperature Rating	Color	Maximum Exposure Temperature	Detector Link Load Ratings		Video Review
					Minimum Load	Maximum Load	
87-120091-165	87-120096-165	165°F (74°C)	Red	100°F (38°C)	0 lb (0 kg)	50 lb (22.7 kg)	87-120096-450
87-120091-212	87-120096-212	212°F (100°C)	Green	150°F (65°C)	0 lb (0 kg)	50 lb (22.7 kg)	87-120096-450
87-120091-286	87-120096-286	286°F (141°C)	Blue	225°F (107°C)	0 lb (0 kg)	50 lb (22.7 kg)	87-120096-450
87-120091-360	87-120096-360	360°F (182°C)	Mauve	300°F (149°C)	0 lb (0 kg)	50 lb (22.7 kg)	87-120096-450
87-120091-450	87-120096-450	450°F (232°C)	Black	375°F (191°C)	0 lb (0 kg)	50 lb (22.7 kg)	87-120096-450
87-120091-500	87-120096-500	500°F (260°C)	Black	435°F (224°C)	0 lb (0 kg)	50 lb (22.7 kg)	87-120096-450

Fusible Metal Detector Link Ratings

Part # (Each)	Detector Temperature Rating	Color	Maximum Exposure Temperature	Detector Link Load		Video Review
				Minimum Load	Maximum Load	
Model ML						
WK-282661-000	165°F (74°C)	Yellow	100°F (38°C)	10 lb (4.5 kg)	40 lb (18.1 kg)	WK-282664-000
WK-282662-000	212°F (100°C)	White	150°F (65°C)	10 lb (4.5 kg)	40 lb (18.1 kg)	WK-282664-000
WK-282664-000	360°F (182°C)	Unpainted	300°F (149°C)	10 lb (4.5 kg)	40 lb (18.1 kg)	WK-282664-000
WK-282666-000	500°F (260°C)	Orange	440°F (226°C)	10 lb (4.5 kg)	40 lb (18.1 kg)	WK-282664-000
Model RGA (A Type)						
87-120060-001	360°F (182°C)	Unpainted	300°F (149°C)	3 lb (1.4 kg)	45 lb (20.4 kg)	