# SECTION 1: COMPANY AND PRODUCT IDENTIFICATION

Manufactured for: Wurth USA Inc

93 Grant Street

Ramsey NJ 07446

Emergency Contact Number: 888-987-8487

Information Telephone Number: 888-987-8487 / www.wurthusa.com

WURTH

Product Name

WUR-HIGHSOLIDS, WUR-HIGHSOLIDS-R

(0893100813, 0893100814, 0893100815, 0893100816)

Recommended Use: Adhesive

#### SECTION 2: HAZARDS IDENTIFICATION

Hazard Classifications: Acute Toxicity - Inhalation: Category 5

Skin Irritation: Category 2
Eye Damage: Category 2A
Reproductive Toxicity: Category 2
STOT Repeated Exposure: Category 2

Aspiration: Category 1
Flammable Liquid: Category 2
Aquatic Hazard - Acute: Category 1
Aquatic Hazard - Long-term: Category 1

GHS Signal Word: DANGERI

Pictograms:



# Hazard Statements:

May cause respiratory irritation.

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Highly flammable liquid and vapor.

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

# Precautionary Statements:

Keep away from heat/sparks/open flames/hot surfaces - no smoking.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Avoid release to the environment.

Use personal protective equipment as required.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lens, if present and easy to do. Continue rinsing.

#### Potential Health Effects

Principal Routes of Exposure Inhalation, skin absorption, eye contact

Acute Effects

Eyes: Contact with eyes may cause irritation. Direct contact with liquid or vapors may cause stinging, tearing, redness,

swelling, and eye damage.

Skin: May cause skin irritation and/or dermatitis. Prolonged or repeated contact or exposure to vapors may cause redness,

burning, and drying and cracking of the skin.

Inhalation: Breathing high concentrations of vapors may cause irritation of the nose and throat or signs of nervous system

depression (i.e. - headache, nausea, drowsiness, dizziness, vomiting, loss of coordination and fatigue).

Ingestion: Ingestion may cause irritation of the digestive tract, nausea, vomiting, and signs of nervous system depression.

Chronic Effects Avoid repeated exposure. May cause blood damage. Repeated contact may cause allergic reactions in very

susceptible persons.

Aggravated Medical Conditions Pre-existing eye, skin, or respiratory disorders may be aggravated by exposure to this product.

#### SECTION 3: COMPOSITION INFORMATION

| Chemical Designation | CAS No.  | % by Weight |
|----------------------|----------|-------------|
| Acetone              | 67-64-1  | 22 - 40%    |
| Hexane               | 110-54-3 | 22 - 40%    |
| Toluene              | 108-88-3 | 5 - 15%     |
| Heptane              | 142-82-5 | 5 - 15%     |

Any remaining ingredients (to comprise 100% of the product) should be considered a proprietary blend of non-hazardous substances, or materials below threshold reporting limits.

#### SECTION 4: FIRST AID MEASURES

General Advice Show this safety data sheet to the doctor in attendance

Eyes: Flush with plenty of cool water for at least 15 minutes, holding eyelids apart for thorough irrigation. If irritation persists, get immediate medical

attention.

Skin: Wash affected area thoroughly with soap and water. Remove contaminated clothing and wash affected areas thoroughly with mild soap. If

skin irritation persists, get immediate medical attention.

Inhalation: Move to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen and get immediate

medical attention.

Ingestion: Do not induce vomiting – seek immediate medical attention. If vomiting occurs, keep head lower than hips to prevent aspiration.

Notes to Physician Treat symptomatically

## **SECTION 5: FIRE FIGHTING MEASURES**

Extinguishing Media: Carbon dioxide, dry chemicals, foam. Water may be helpful in keeping adjacent containers cool; avoid spreading the liquid with water used

for cooling. Water-based sprinkler systems may help contain larger fires.

Specific Hazards arising

from the Chemical

Closed containers may rupture if exposed to fire or extreme heat. May produce toxic fumes if burning.

Special protective

Equipment:

Wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protective equipment. Remove all sources of ignition.

Environmental Precautions Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from

entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot

be contained.

Methods for Clean-up Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface

thoroughly.

Other Information None known

#### SECTION 7: HANDLING & STORAGE

Handling: Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Wear appropriate personal protective

equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of

the equipment must be grounded. Keep away from open flames, hot surfaces and sources of ignition.

Storage: Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from extremes of heat or cold. Keep in properly labeled

containers.

# SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

### **Exposure Limits**

| Hazardous Components | OSHA PEL | ACGIH TLV |
|----------------------|----------|-----------|
|                      |          |           |
| Acetone              | 1000     | 250       |
| Hexane               | 500      | 50        |
| Toluene              | 200      | 20        |
| Heptane              | 500      | 400       |

**Engineering Measures** Ensure adequate ventilation, especially in confined areas.

Select and use personal protective equipment based on the results of an exposure assessment. The personal protective equipment listed below is recommended:

# Personal Protective Equipment

**Eyes/Face:** Safety goggles or glasses, or full face shield.

Skin: Protective gloves and impervious clothing. Consult the glove/clothing manufacturer for proper selection of materials.

Respiratory Protection: In operations where exposure limits are exceeded, use a NIOSH-approved respirator that has been selected by a technically qualified

person for the specific work conditions.

Hygiene Practices: Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

When using, do not eat, drink or smoke.

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Yellow or red liquid.

Odor: Solvent odor.
Odor Threshold No data

 VOC (g/L)
 392

 VOC (g/L) less exempt & water
 549

 Non-volatile (wt%)
 24.50

 Specific Gravity (g/l)
 0.819

 Bulk Density (lb/gal):
 6.82

Solubility in Water Insoluble

pH Not available

Viscosity Not available

Evaporation rate : Faster than nBuAc

Vapor Pressure (mmHg): Not available

Vapor Density : Heavier than air

Boiling Point: 133.0 °F [56.1 °C]
Freezing/Melting Point: Not determined

Flammability (solids):

Partition Coefficient (n-octonal/water)

No data

Auto-ignition Temp:

No data

Decomposition Temp:

No data

Explosive Properties:

No data

Flash Point: -20.0 °F [-28.9 °C]

Flammable Limits: Lower: 1.66; Upper: 9.22

# SECTION 10: STABILITY AND REACTIVITY

Oxidizing Properties:

Chemical Stability: Stable under normal conditions. Hazardous polymerization does not occur.

No data

Conditions to Avoid: Keep away from open flames, hot surfaces, static electricity and sources of ignition. Avoid extremes of heat or cold.

Materials to Avoid: Incompatible with strong acids and bases, alkali metals, halogens, and strong oxidizing agents.

Hazardous Decomposition Products: Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide, carbon dioxide, smoke, and other

unidentified organic compounds may be formed during combustion.

Possibility of Hazardous Reactions: None under normal conditions of use.

### SECTION 11: TOXICOLOGICAL INFORMATION

Reproductive Toxicity: Category 2 Acute Toxicity: Oral: No data; Skin: No data; Inhalation: Category 5

Mutagenicity: No data Irritation: Skin: Category 2 STOT-single exposure: No data Corrosivity: No data

STOT-repeated exposure: Category 2 Sensitisation: Respiratory: No data; Skin: No data
Aspiration Hazard: Category 1 Typical Routes of Entry: Inhalation, skin absorption, eye contact

#### Chronic Toxicity / Carcinogenicity

Component IARC NTP OSHA

### SECTION 12: ECOLOGICAL INFORMATION

Aquatic Toxicity: Acute and prolonged Toxicity to Fish:

No data

Acute Toxicity to Aquatic Invertebrates: No data Environmental Fate and Pathways: No data

Persistence and Degradability: No data
Bioaccumulative Potential: No data
Mobility in Soil: No data

Other Adverse Effects: No data

### SECTION 13: DISPOSAL CONSIDERATION

Waste Disposal Method

Dispose of in accordance with all applicable local, state, and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

# SECTION 14: TRANSPORT INFORMATION

## FIVE-GALLON PAILS OR LARGER

REGULATION

DOT

Proper Shipping Name ADHESIVES

 Hazard Class
 3

 UN-No
 UN1133

 Packing Group
 PGII

Pictograms:

ICAO / IATA

IMDG/IMO



Contact the preparer for further information.

Contact the preparer for further information.

DESCRIPTION

#### ONE-GALLON CONTAINERS OR LESS

REGULATION DESCRIPTION

DOT

Proper Shipping Name This product may ship as a LIMITED QUANTITY

Hazard Class UN-No Packing Group

### Pictograms:

ICAO / IATA IMDG/IMO Contact the preparer for further information. Contact the preparer for further information.

### **SECTION 15: REGULATORY INFORMATION**

US TSCA:

Yes - All components are listed or exempt

OSHA Regulatory Status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

#### **SARA 313**

Section 313 OF Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). If listed below, this product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

| Chemical Designation | Cas No.  | Weight % |
|----------------------|----------|----------|
| Hexane               | 110-54-3 | 22 - 40% |
| Toluene              | 108-88-3 | 5 - 15%  |

### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPS) (see 40 CFR 61)

| Chemical Designation | Cas No.  | Weight % |
|----------------------|----------|----------|
| Hexane               | 110-54-3 | 22 - 40% |
| Toluene              | 108-88-3 | 5 - 15%  |

### State Regulations

# California Proposition 65

This product contains the following substance(s) known to the state of California to cause cancer or reproductive harm:

 Chemical Name
 CAS Number

 Toluene
 108-88-3

## SECTION 16: OTHER INFORMATION

NFPA is a Health, Flammability and Reactivity rating: 230B

4 - SEVERE HAZARD, 3 - SERIOUS HAZARD, 2 - MODERATE HAZARD, 1 - SLIGHT HAZARD, 0 - MINIMAL HAZARD, \* - Chronic Hazard

Date printed: 9/19/2017 SDS Review Date: 05/22/2017

The above Information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith. No warranty is implied with respect to the quality or the specification of the product and the user must satisfy his self that the product is entirely suitable for his purposes.

\*\*\*\*\* END OF SAFETY DATA SHEET \*\*\*\*\*