


Salice Hinge Kits



1.

Depth Adjustment Cam

The horizontal (lateral) adjustment range is 6mm.

The depth adjustment range is 3.1 mm (-0.5mm to +2.8mm) for all hinge bases.
2.

Horizontal (Lateral) Adjustment Cam

The horizontal (lateral) adjustment range is 6mm (-1.5mm to +4.5mm for 35mm cup hinges; -0.5mm to +5.5mm for 40mm cup hinges), while maintaining a constant gap behind the door.
3.

Vertical (Height) Adjustment Cam

The vertical (height) adjustment range is 4mm (-2mm to +2mm).

Features

- Three-way cam hinges for easy adjustment
- Horizontal, vertical and depth changes can be made without loosening any screws
- Four types of hinges for a variety of application

Clearance: 8080 HKS standard hinge: 1-21/32"
8080 HKF free swing hinge: 1-21/32"
8080 HKL partial overlay hinge: 1-37/64"
8080 HKX extra thick door hinge: 1-37/64"

Finish: Black (BLK), Nickel (NP)

Configurations

Pack Configurations		Hinge Base	Hinges	Screws	Cover Caps
Kit (K)	2 per bag; 10 bags per carton	Yes	Yes	Yes	Yes
Nickel (NP) Finish Salice Hinges for Use with 8071, 8081, 8091 Pocket Door Slides					
Kit (K)	Hinge Cup Size		Door Thickness	Application	
8080 HKS SAL	35 mm		3/4"	Inset	
8080 HKF SAL	35 mm		3/4"	Inset - Free Swing	
8080 HKL SAL	40 mm		3/4"	Overlay	
8086 HKX SAL	40 mm		1-1/4"	Inset - Thick Door	
Black (EB) Finish Salice Hinges for Use with 8071, 8081, 8091 Pocket Door Slides					
Kit (K)	Hinge Cup Size		Door Thickness	Application	
8080 HKS SAL EB	35 mm		3/4"	Inset	
8080 HKL SAL EB	40 mm		3/4"	Overlay	
8086 HKX SAL EB	40 mm		1-1/4"	Inset - Thick Door	