


IXIO-DT1

ACTIVATION AND SAFETY SENSOR FOR AUTOMATIC SLIDING DOORS



PRIMARY APPLICATIONS



DESCRIPTION

BEA's IXIO-DT1 is the premier activation and safety sensor, combining the highest quality and the best value for the automatic sliding door industry.

This dual technology product is a highly flexible and user-friendly solution for sliding doors, industrial doors, vehicle gate detection and off-door automation.


The IXIO-DT1 can be adjusted into an ANSI compliant solution and has earned a comprehensive list of credentials and certifications, including UL, FCC and IP54.

The IXIO-DT1 ensures convenience, safety and energy efficiency for all BEA customers and end users.

FEATURES & BENEFITS

- Ten microwave activation sensitivity settings and three infrared safety immunity settings
- Ability to distinguish between approaching and departing traffic
- Two 24 spot, high-density, infrared safety curtains providing precise presence detection
- Four visible red alignment spots are projected on the ground to assist in precise IR curtain adjustment
- Intelligent programming and troubleshooting via a menu-driven LCD
- On-board microprocessor optimizes data analysis, monitors sensor performance and enables system integration
- Fully monitored internally, capable of external monitoring


APPLICATIONS



TECHNICAL SPECIFICATIONS

Technology	Microwave Doppler Radar	Active Infrared
Detection Mode	Motion	Presence
Transmitter Frequency	24.150 GHz	N/A
Transmitter Radiated Power	< 20 dBm EIRP	N/A
Transmitter Power Density	< 5 mW/cm ²	N/A
Spot Size	N/A	2 in x 2 in
Max. Number of Spots	N/A	24 per curtain
Max. Number of Curtains	N/A	2
Output	Electro-mechanical-relay (potential and polarity free)	Solid-state-relay (potential and polarity free)
Max. Contact Power	15 Watts	N/A
Max. Contact Current	1 A	400 mA
Max. Contact Voltage	30 VDC	42 VDC
Hold Time	Microwave: 0.5 to 9 s (user adjustable)	Infrared: 0.3 s if < 4 s*, 1 s if ≥ 4 s* (*if in detection for)
Test Input	N/A	Sensitivity: Low:<1 V; High:> 10V (max.30V) Response time on test request: typical:<5ms
Supply Voltage	12 to 24 VAC 50/60 Hz 12 to 30 VDC	
Power Consumption	< 2.5 W	
Mounting Height	78 in - 138 in (6.5 ft - 11.5 ft)	
Temperature Range	Sensor: -31°F to +131°F LCD: 14°F to +131°F 0 to 95% relative humidity, non condensing	
Degree of Protection	IP54	
Norm Conformance	R&TTE 1999/5/EC; EMC 2004/108/EC; MD 2006/42/EC; RoHS 2002/95/EC	
Dimensions (D x W x H)	2.25 in x 10.6 in x 2.27 in	
Cable Length	360 in (30 ft)	


DIMENSIONAL DRAWINGS




RELATED PRODUCTS



10IXIODT1V
DUAL TECHNOLOGY
SENSOR WITH VIDEO



10IXIOST
IR ONLY
SENSOR



10IMB
MOUNTING BRACKET
ADAPTER




10IRA
RAIN
ACCESSORY




10ICA
FLUSH MOUNT
CEILING ADAPTER



35.1286
BLACK REPLACEMENT
COVER



35.1303
SILVER REPLACEMENT
COVER



35.1302
WHITE REPLACEMENT
COVER



10REMOTEBEA
UNIVERSAL
REMOTE CONTROL

www.BEAinc.com

© 2015 BEA, Inc. All rights reserved.

IXIO-DT1

ACTIVATION AND SAFETY SENSOR FOR AUTOMATIC SLIDING DOORS

BEA, Inc.
RIDC Park West
100 Enterprise Drive
Pittsburgh, PA 15275-1213

Customer Service: 800.523.2462
Technical Support: 800.407.4545

