INNOVATIVE FEATURES

The 4100-10 Worksite Table Saw includes a Bosch-exclusive electronics package. Soft-start circuitry mitigates the intensity of motor start-up and minimizes the chance of tripping a circuit breaker; constant speed circuitry helps maintain cutting speed under load; overload protection is included. The Smart Guard System is the first modular table saw blade guard system, featuring a three-position adjustable riving knife, anti-kickback pawls and non-obstructed-view barrier guard assembly. The entire system attaches and detaches in seconds, doesn't interfere with the work and stores on the tool.

Bosch Innovation

10" WORKSITE TABLE SAW WITH GRAVITY-RISE WHEELED STAND
4100-10

SOFT START | CONSTANT SPEED | ELECTRONIC MOTOR PROTECTION | ON TOOL STORAGE | SPINDLE LOCK | DOUBLE INSULATION

▸ Bosch-Exclusive Electronics—Includes soft-start, Constant Response circuitry to maintain speed under load and overload protection
▸ Smart Guard System—Quick-to-install and easy-to-use modular blade guard; anti-kickback pawls and riving knife system provide superior control over material while cutting
▸ SquareLock Rip Fence—Engineered for maximum trueness
▸ Integrated Sub-Base—Increases tool life by protecting table saw base
▸ Gravity-Rise Stand—For easy setup and take down of table saw
▸ 8 In. Wheels with Solid Rubber Like Tires—Handle tough terrain

INCLUDES
10 In. Carbide-Tipped Blade
Rip Fence **2610950148**
Miter Gauge **2610950149**
Smart Guard System
    Barrier-Guard Device **2610950092**
    Anti-Kickback Pawls **2610950093**
Push Stick **2610950112**
Throat Plate Insert **2610950090**
Gravity-Rise Wheeled Table Saw Stand

SPECIFICATIONS	
RATING	120V
AMPERAGE	15.0
NO LOAD RPM	3,650
MAX. MOTOR HP	4.0
BLADE DIAMETER	10"
DADO SIZE	13/16" (8" or less)
ARBOR SIZE	5/8"
RIP FENCE CAPACITY	25" (R)
DEPTH OF CUT AT 90°	3-1/8"
BEVEL RANGE	-2°–47°
TABLE TOP DIMENSIONS	29" × 21-1/2"
EXTENDED WIDTH OF TABLE TOP	40.5"
SAW WEIGHT	63.0 lbs.
STAND WEIGHT	29.0 lbs.

Dust collection attachments available on page 324.