



GCM12SD 12" Dual-Bevel Glide™ Miter Saw



- ▶ Expanded Cutting Capacity: 14" horizontal capacity (nominal); 6-1/2" vertical capacity against the fence (base); 6-1/2" crown capacity against the fence (45° spring)
- ▶ Upfront-Bevel Controls—All-metal bevel lock lever and range selector located upfront for quick and easy bevel settings without reaching behind the saw
- ▶ SquareLock™ Quick-Release Fences: High-precision squarelock fence aligns 90° to table and requires no adjustment; one-touch lock/unlock to slide fence for added support

Includes:

Carbide-Tipped Blade
 Wrench **1609B00256**
 Toolless Vertical Work Clamp **1609B02315**
 Dust Bag/Elbow **1609B00506/1609B00505**

Optional dust collection attachments available on page 274.

Specifications	
Rating	120V
Amperage	15
No Load RPM	3,800
Blade Diameter	12"
Arbor Size	1"
Bevel Angle Range	47° left/47° right
Bevel Detents/Stops	0°, 33.9°, 45°, 47° left/right
Miter Angle Range	52° left/60° right
Miter Detents	0°, 15°, 22.5°, 31.6°, 45° (left/right) 60° (right)
Crown Molding Angled	6-1/2" max
Base Molding Against Fence	6-1/2" max
Miter/Bevel (Nominal)	0 miter × 0 bevel—4" × 14" 45 miter × 0 bevel—2" × 10" 0 miter × 45 bevel—2" × 14"
Height	27"
Depth	32-3/8"
Width	26-1/2"
Weight	65.0 lbs.



GLM 80 + R 60 Laser Distance Measurer with 24" Digital Level Attachment

Combining the Bosch GLM 80 two-axis laser distance and angle measurer powered by Lithium-Ion technology with the R 60 digital level attachment automatically creates a 24" digital level.

See page 288 for more information on the GLM 80 + R 60.