

MRF23EVS 2.3 HP Electronic Fixed-Base Router



- ▶ Trigger-Control System—Trigger power switch (with lock-on button) conveniently located in handle for enhanced control
- ▶ Always-On Dual LED Lighting—For enhanced visibility in bit area
- ▶ Variable-speed dial, soft-start and Constant Response™ circuitry
- ▶ MRF01 fixed base with macro- and micro depth setting system with ability to adjust depth from above a router table

Includes:
Fixed Base **MRF01**
1/4" Self-Releasing Collet Chuck **2610906283**
1/2" Self-Releasing Collet Chuck **2610906284**
16mm Shaft Wrench **2610991388**
24mm Collet Nut Wrench **2610992417**
T-Handle Hex Wrench **2610923193**
(3) M4 Screws for Table Mounting

Optional dust collection attachments available on pages 228–229 and 274.

Specifications	
Rating	120V AC
Amperage	15
Max. Tool HP	2.3
No Load RPM	10,000–25,000
Fixed-Base Continuous Depth Range	1-5/8"
Fixed-Base Macro Depth Steps (3)	1/2"
Subbase/Base Openings	2"/3.75"
Height	9.5"
Weight	9.3 lbs.

MRP23EVS 2.3 HP Electronic Plunge-Base Router



- ▶ Trigger-Control System—Trigger power switch (with lock-on button) conveniently located in handle for enhanced control
- ▶ Always-On Dual LED Lighting—For enhanced visibility in bit area
- ▶ Variable-speed dial, soft-start and Constant Response™ circuitry
- ▶ MRP01 Plunge Base with Smooth Plunge Action, Spring-Lock Plunge Lever and Depth Rod—For easy and precise plunge routing

Includes:
Plunge Base **MRP01**
1/4" Self-Releasing Collet Chuck **2610906283**
1/2" Self-Releasing Collet Chuck **2610906284**
16mm Shaft Wrench **2610991388**
24mm Collet Nut Wrench **2610992417**

Optional dust collection attachments available on pages 228–229 and 274.

Specifications	
Rating	120V AC
Amperage	15
Max. Tool HP	2.3
No Load RPM	10,000–25,000
Plunge Depth	3"
Plunge-Base Afterlock Adjustment Range	5/8"
Subbase/Base Openings	2"/3.32"
Height	12"
Weight	12.6 lbs.

MRC23EVSK 2.3 HP Electronic Modular Router System



- Same features as MRF23EVS and MRP23EVS above.**
- ▶ Includes MRF01 Fixed Base and MRP01 Plunge Base
 - ▶ Easy-to-pack case

Includes:
Fixed Base **MRF01**
Plunge Base **MRP01**
1/4" Self-Releasing Collet Chuck **2610906283**
1/2" Self-Releasing Collet Chuck **2610906284**
16mm Shaft Wrench **2610991388**
24mm Collet Nut Wrench **2610992417**
T-Handle Hex Wrench **2610923193**
(3) M4 Screws for Table Mounting
Carrying Case **2610913367**

Optional dust collection attachments available on pages 228–229 and 274.

Specifications	
Rating	120V AC
Amperage	15
Max. Tool HP	2.3
No Load RPM	10,000–25,000
Fixed-Base Continuous Depth Range	1-5/8"
Fixed-Base Macro Depth Steps (3)	1/2"
Plunge Depth	3"
Plunge-Base Afterlock Adjustment Range	5/8"
Subbase/Base Openings	2"/3.75" (fixed) 2"/3.32" (plunge)
Height	9.5" (fixed)/ 12" (plunge)
Weight	9.3 lbs. (fixed)/ 12.6 lbs. (plunge)