T-Shank Jig Saw Blades

Wood							Shank	
Item #	Qty.	Cut Type	Application	TPI	Blade Material	Overall Length	Working Length	Blade Thickness
T308B	5	Xtra-Clean For Wood						
T308B25	25	Straight, tear free on top and bottom surface	Wood, laminated particle board, MDF	12	HCS	4-1/2"	3-1/2"	0.05"
Т308ВО	5	Xtra-Clean For Wood Scroll blade for curved cuts	Wood, laminated particle board, MDF	12	HCS	4-1/2"	3-1/2"	0.05"
T234X3	3	Progressor For Wood Straight, accurate, splinter free	Thick/thin, hard/soft woods including OSB, particle board, plywood, laminated particle board	8-12 P	HCS	4-1/2"	3-17/32"	0.06"
T234X	5							
T234X25	25							
T101D	5	Clean For Wood	Hard/soft woods, plywood, OSB,	5-6	HCS	4"	3"	0.06"
T101D100	100	Straight, clean	plastics 1/4"-2-3/8"	5-6	нсэ	4	3	0.06
T301DL	5	Clean For Wood Straight, Clean	Hard/soft woods, plywood, OSB, plastics 1/4"-3-3/8"	6	HCS	5"	4-1/8"	0.06"
T301CD	5	Clean For Wood Straight, medium-fine	Hard/soft woods, plywood, laminated particle board 3/16"-2-3/8", plastics 3/16"-1-1/4"	8	HCS	4-5/8"	3-5/8"	0.06"
T101B3	3	Clean For Wood - Straight, fine	Hard/soft woods, plywood, plastics, OSB, laminated particle board 3/16"-1-1/4"	10 V	HCS	4"	3"	0.06"
T101B	5							
T101B100	100							
T101BR T01BR100	5	Clean For Wood Reverse tooth, splinter free	Hard/soft woods, plywood, OSB, laminated particle board, plastics	10	HCS	4"	3"	0.06"
		on top of surface Clean For Wood	3/16"-1-1/4"					
T101A03	3	Curved cuts with splin- ter free on both sides of	Double-sided laminates, laminated particle board, MDF, hard/soft woods, plywood 5/64"–3/4"	20	HCS	3-1/4"	2-5/16"	0.05"
T101A0	5							
T101A0100	100	surface						
T101BF	5	Clean For Hardwood Long life, straight, fine cuts	Hard/soft woods, plastics, plywood, laminated particle board 3/16"-1-1/4"	10 V	Bi-metal	4"	3"	0.05"
T101DP	5	Precision For Wood Precise right angle cuts	Hard/soft woods, plywood, particle board, plastics 1/4"-2-3/8"	6	HCS	4"	2-3/4"	0.07"
T144DP	5	Precision For Wood Precise right angle cuts	Hard/soft woods, laminated particle board, plywood 3/16"–2"	6	HCS	4"	2-7/8"	0.07"
T344DP	5	Precision For Wood Precise right angle cuts	Hard/soft woods, laminated particle board, plywood 3/16"-4"	6	HCS	6"	5"	0.07"
T144D3	3	Speed For Wood - Straight and very fast	Hard/soft woods, OSB, plywood, 1/4"–2-3/8"	5-6	HCS	4"	3"	0.05"
T144D	5							
T144D100	100							
T244D3	3	Speed For Wood Scroll blade for curved and fast cuts	Hard/soft woods, OSB, plywood, 1/4"–2-3/8"	5-6	HCS	4"	3"	0.05"
T244D	5							
T244D100	100							
T344D	5	Speed For Wood Straight and very fast	Hard/soft woods up to 4"	6	HCS	6"	5"	0.05"
T744D	5	Speed For Wood Straight and very fast	Hard/soft woods up to 5-5/16"	6	HCS	7"	6"	0.07"
T144DF	5	Speed For Hardwood Straight, very fast with long life	Hard/soft woods, OSB, plywood, wood with nails 1/4"-2-3/8"	5-6	Bi-metal	4"	2-3/4"	0.05"
T344DF	5	Speed For Hardwood	Hard/soft woods, OSB, plywood, wood with nails 1/4"-4"	6	Bi-metal	6"	5"	0.05"
T111C3	3	Basic For Wood Fast, coarse cuts. Ideal for jigsaws without orbital action	Softwood, OSB, plywood 7/32"-2-3/8"	8	HCS	4"	3"	0.05"
T111C	5							
T119BO3	3	Basic For Wood	Softwood, OSB, plywood, 5/16"-1/4"	12	HCS	3-1/4"	2-3/16"	0.04"
T119BO	5	Scroll blade for curved cuts	3011w00d, O3B, piyw00d, 5/16"-1/4"	12	псэ	3-1/4"	2-3/16"	0.04
T101BIF	5	Special For Laminate Straight, splinter free	Laminate flooring	14	Bi-metal	3-1/4"	2-5/16"	0.05"
T101AOF	5	Special For Laminate Scroll blade for curved, splinter free. Ideal for jig- saws without orbital action	Laminate flooring	20	Bi-metal	3-1/4"	2-5/16"	0.05"