



- ☑ Surface-Mounted
- ☑ ADA compliant – opens with less than 5 lbs. of force, projects less than 4" from the wall when closed
- ☑ Model 9631 – Light Grey **Bradex**®
- ☑ Model 9632 – Cream **Bradex**®

Product Materials

Bacterial resistant high density polyethylene with steel to steel support hinges. Pneumatic gas shock mechanism opens and closes unit smoothly. Liner dispenser and purse.diaper bag hooks molded in. ADA compliant nylon buckle is adjustable with one hand.

STRENGTH NOTE: Unit complies with ASTM F2285 Standard that requires commercial diaper changing stations be able to support a static load of up to 250 lbs.

Installation


Verify all rough-in dimensions prior to installation. Secure to wall through mounting holes. Mounting hardware for typical conditions is included.

⚠ WARNING: Be sure to use reinforced backing behind wall where mounting screws or anchoring devices are installed to ensure adequate support for the baby changing station. All anchoring devices must be appropriate for specific wall construction. Severe personal injury and/or property damage may result from improper mounting.

Guide Specification

Surface-mounted baby changing station shall be solid light grey (9631) or cream colored (9632) molded bacterial-resistant, high density polyethylene. Steel to steel support hinges with pneumatic gas shock mechanism. Unit shall have integrated liner dispenser and bag hooks. Unit shall have an anti-microbial safety belt. Warning labels are printed in English, Spanish, French and Braille. Unit shall be operable with less than 5 lbs. of force and complies with ASTM F2285 Standard.

Overall dimensions: 34-1/4"W x 15-3/8"H x 4"D.



ADA Compliant

- ☑ Consult local and national accessibility codes for proper installation guidelines.
- ☑ Conformity and compliance to local and national codes is the responsibility of the installer.

Service Parts Available

Part Number	Description
P15-491	Replacement Strap

Orders composed of products indicated as **Bradex**® will be available to ship in three days after receipt of order at the factory. There is no pricing penalty for this service from Bradley.