


MJF



1. Adapter Body
2. High Temp. Gasket
3. Lock Washer
4. Gasket Nut

INSTRUCTIONS FOR INSTALLATION OF "JIFFY PLUG" ADAPTERS

1. MAKE A HOLE IN THE SHEET METAL USING THE REFERENCE GUIDE (OPPOSITE).
2. INSTALL THE GASKET ON THE ADAPTER BODY.
3. INSERT THE ADAPTER INTO THE HOLE AND INSTALL THE LOCK WASHER FIRST THEN THE GASKET NUT.
4. HAND TIGHTEN THE GASKET NUT AND USING A WRENCH APPLY A FURTHER HALF TURN (TO PROVIDE THE TORQUE SPECIFIED).

BAG P/N:10022 CHINA



FITTINGS FOR HOOD AND DUCT PENETRATION 2L09

JIFFY-PLUG™ REFERENCE GUIDE

USED FOR	7/8" PLUG	1 1/8" PLUG	1 5/8" PLUG
JIFFY P/N	393PJ	395PJ	399PJ
HOLE SIZE	φ 7/8"	φ 1-1/8"	φ 1-5/8"
GASKET NUT TORQUE	25 FT-LB	50 FT-LB	50 FT-LB
CONTENTS	✓		

 **Jiffy**™
SEAL