



## ***I. Product Description***

**CRC Carb & Choke Cleaner** is a fast-acting carburetor and choke cleaner that dissolves carburetor deposits such as sludge, gum and varnish. Its low VOC formula is designed to maximize carburetor performance, improve fuel system performance and ensure maximum fuel economy.

## ***II. Applications***

Recommended for cleaning automatic chokes, carburetor elements, intake parts and ventilating systems. Suitable for general purpose cleaning of non-painted surfaces.

## ***III. Features & Benefits***

- Effectively Dissolves Harmful Deposits.** Removes gum, sludge and varnish that inhibit performance.
- Fast-Acting.** Efficient cleaning action.
- Safe for Equipment.** Will not harm oxygen sensors or catalytic converters.
- Low VOC Formula.** Reduces contributions to ground smog. Meets U.S. EPA and CA VOC requirements.
- Improves Fuel System Performance.** Ensures maximum fuel economy.
- M.S.D.[L.]™-Material Safety Data Label.** Provides instant access to current safety information should an accident or OSHA inspection occur. Helps comply with **OSHA Hazard Communications Standard 29 CFR 1910.1200**.

## ***IV. Physical Properties without propellant***

<b>Flash Point</b>	<0°F TCC	<b>Boiling Point</b>	131°F (initial)
<b>Odor</b>	Aromatic	<b>Solubility</b>	Slight in H <sub>2</sub> O
<b>Appearance</b>	Clear, colorless liquid	<b>VOC %</b>	45%
<b>Vapor Density</b>	Heavier than air	<b>Specific Gravity</b>	0.815
<b>Vapor Pressure</b>	Not Determined	<b>Freezing Point</b>	Not Determined
<b>VOC Content (Fed)</b>	366 g/L	<b>pH</b>	N/A
<b>Sara Title III, Sect. 313 Chemicals</b>	Yes	<b>% VOC</b>	75%
<b>Prop 65</b>	Yes	<b>Propellant</b>	Carbon Dioxide

## ***V. Specifications and Approvals***

Not applicable.

## ***VI. Performance Characteristics***

Not applicable.

## VII. Directions

Read all directions before using this product. Use plastic extension tube to direct spray to exact location.

### CARBURETOR AND LINKAGE

- With ignition off and engine cool, remove air filter and entire exterior surface of carburetor including linkage.
- After carburetor dries, start engine and spray **CRC Carb & Choke Cleaner** down the carburetor throat to remove the deposits from the lower throttle plate area.

### AUTOMATIC CHOKES

- With engine off, spray **CRC Carb & Choke Cleaner** on both ends of choke valve and corresponding linkages while opening and closing choke by hand.

### MANIFOLD HEAT CONTROL VALVE

- With engine cold, spray **CRC Carb & Choke Cleaner** on both ends of heat control valve shaft.
- Move counterweight up and down until valve moves freely. If necessary, tap gently with a light hammer to loosen a frozen heat control valve.

### PCV VALVES

- Disconnect crank case side of PCV valve and, with the engine running, spray **CRC Carb & Choke Cleaner** into open end of valve while working the plunger back and forth.

### IMPORTANT

- If spilled or sprayed on painted surface, wipe off or wash off immediately.

## VIII. Package Description

Part Number	Container Size
03077	16 oz Aerosol

## IV. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

## X. Special Use Warnings

### Aerosol Cans

Contents extremely flammable. Do not smoke while spraying. Extinguish all flames, pilot lights, and heaters. Do not puncture, incinerate or store above 120° F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

### General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Vapors will accumulate readily and may ignite. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

**PRODUCT WARRANTY:** CRC offers a conditional warranty on this product for the period of 2 years from the date of manufacture.

**DISCLAIMER:** This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.