



Specifications:

CATO Protective Covers



Cato 220-SB



Easy to install in minutes



Easy to use

FEATURES:

- Made in the U.S.A.
- Can be installed in a very few minutes
- Can be installed with a screwdriver
- Mounting screws and anchors provided
- No glass to shatter
- Scored acrylic panel for easier emergency access
- Cannot rust
- Rounded corners for maximum safety
- Easily kept clean
- Opened quickly for inspection or maintenance
- Greater impact-resistance than metal
- Lower shipping/handling costs than metal
- Water-resistant for outside installation
- Injection molded of high density plastic

HIGHLIGHTS:

- Shipped completely assembled
- Cover remains open during inspection/maintenance
- Pull handles are designed to A.D.A. specifications
- Breaker bar is vandal-resistant
- Available with breaker bar or unsecured pull handle

SPECIFICATIONS:

Protective covers, as manufactured by Cato, with body and hinged cover injection molded of high-density red polyethylene and scored acrylic break panel with UV resistant instruction label. If model with breaker bar is specified, the bar is galvanized steel and is attached to the cover with nylon-coated steel cable. Covers with pull handles are integrally molded of copolymer polypropylene and have a UV resistant "Pull To Open" label. All covers come standard with two UV resistant side labels for easy locating of alarm pull station.



Specifications:

CATO Protective Covers

Pull To Open Cato Covers

FEATURES:

- Pull to open access
- Reduces vandalism
- Reduces false alarms
- No breaker bar
- Outdoor and indoor applications
- Ultraviolet inhibitors

OPTIONS:

GASKET (X) - The gasket is uniquely extruded with an air pocket, which allows water-tight installation on stucco and other rough, uneven surfaces.



Cross section
of gasket


GERONIMO ALARM (A) - The alarm is battery operated and will sound when the magnetic field is broken. Geronimo's battle cry is loud enough to virtually eliminate false alarms.



220-S

PULL TO OPEN

CL-418
Pull To Open Label



CL-419
Break Panel Label



CL-420
Side Label

Cover Catalog Number	Cabinet Minimum Inside Dimensions						Cabinet Maximum Outside Dimensions						Glass Panel		Carton Quantity	Carton Shipping Weight Each				
	Height		Width		Depth		Height		Width		Depth									
	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.								
220-R, 230-R	7 1/4	188	6 1/4	163	1 3/4	47	8 1/4	210	7 1/2	189	2 1/4	60	6 sq. in.	152 sq. in.	1	1.5				
220-S, 230-S	7 1/2	193	6 1/2	167	3 1/4	84	8 1/4	213	7 1/2	193	3 3/4	95	6 sq. in.	152 sq. in.	1	1.7				



Specifications:

The Chief Fire Extinguisher Cabinet



Chief 105-5 WWC-H



10008
Stainless Steel Breaker Bar



10011R
Red Hammer Assembly



10011W
White Hammer Assembly

FEATURES:

- Made in the U.S.A.
- Cannot rust
- No sharp corners
- No glass to shatter
- Pitched drainage
- Natural ventilation
- Dent-proof
- Lower freight cost
- Less storage space
- Easily cleaned
- No padlock required
- High density injection molded
- All sizes in red or white
- Lower replacement costs

HIGHLIGHTS:

- Cylinder lock with key
- Red or white injection molded plastic hammer with flexible torsion and ribbed grip
- Stainless steel clear nylon jacketed mechanical cable
- Grid-scored, UV-resistant break panel for improved emergency access
- UV-resistant labels
- Protective frame
- Lower maintenance cost

CATO CHIEF - SECOND TO NONE

Cato has been providing the quality Chief fire extinguisher cabinets since 1984. The Chief cabinets protect the extinguisher from weather and any ambient conditions that might jeopardize its use. The elimination of metal reduces the chance of personal injuries and reduces the possibilities of product liability insurance claims. The unique design of the Chief cabinets also reduces vandalism and theft.



Specifications:

The Chief Fire Extinguisher Cabinet

SPECIFICATIONS:

Fire Extinguisher Cabinet, as manufactured by Cato, Inc., with body and frame injection molded of red or white virgin high-impact crystal polystyrene of .110 wall thickness with ultra-violet inhibitors, virgin acrylic Plaskolite® panel of .080 thickness, cylinder lock and key, polypropylene plastic injected molded hammer with flexible torsion, ribbed grip surface, and clear nylon-jacketed stainless steel mechanical cable.

- 105-5 Chief is for 5 or 2 1/2 lb. extinguisher.
- 105-10 Chief is for 10 lb. extinguisher.
- 105-20 Chief is for 20 lb. extinguisher.

Red bodies shipped with red hammer.

White bodies shipped with white hammer.




105 RRC



105 WWC



CL-401 Label

CL-415
Break Panel LabelCL-416
Pull Panel LabelIsland Chief w/ clear pull panel
"Tampering is a Felony" label
5 or 10 lb. extinguisher sizes.

Chief Catalog Number	Cabinet Minimum Inside Dimensions						Cabinet Maximum Outside Dimensions						Cabinet With Cover Maximum Outside Dimensions						Ctn.	Carton Shipping Weight		
	Height		Width		Depth		Height		Width		Depth		Height		Width		Depth					
	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.				
105-5	16 3/4	419	6	150	5 3/8	135	19	475	8	200	6 3/8	166	19 1/4	482	8 1/4	207	6 3/4	169	12	41	19	
105-10	20 1/2	513	6 3/4	169	6	150	23	575	9	225	7	175	23 1/4	582	91/4	232	7 1/4	182	10	44	20	
105-20	26	650	9	225	8	200	28	700	11	275	9	225	28 1/2	713	11 1/2	288	9 1/2	238	4	32	14	



THE WARRIOR FIRE EXTINGUISHER CABINET

FEATURES:

- Made in the U.S.A.
- Cannot rust
- No sharp corners
- No glass to shatter
- Pitched drainage
- Natural ventilation
- Dent-proof
- Lower freight cost
- Less storage space
- Easily cleaned
- No padlock required
- High density injection molded
- All sizes in red or white
- Lower replacement costs
- 95-5 for 5 lb. Extinguisher
- 95-10 for 10 lb. Extinguisher

HIGHLIGHTS:

- Locking seal
- Two-piece construction
- No breaker bar
- Pulls up to remove cover
- Side labels included
- Convertible to a Chief

SPECIFICATIONS:

Fire Extinguisher Cabinet, as manufactured by Cato, Inc. with cabinet body injection molded of linear, high density red or white virgin high-impact polystyrene of .110 wall thickness with ultra-violet inhibitors and high-impact crystal polystyrene .100 wall thickness one-piece cover.

Warrior bodies are available in red or white. Warrior covers are available in clear or red.



CWS 401



CL401



CL426



CL413



CL403




EWH-H

EWH-F



CL416



CL415



CL416A

PULL TO OPEN

CL418



CL419



CL422



CL420



CL421



Specifications:

THE CATO CRAFTSMAN

THE CATO CRAFTSMAN

DELUXE SOLID MAPLE EXTINGUISHER CABINETS



Semi-Recess
Shaker Cherry Stain
Catalog Number 51001
Description 505-10 SR
Variety of stains available



Fire Extinguisher Cabinet, as manufactured by Cato, Inc., with Solid Maple Dovetail Construction, 1 inch wall thickness (Semi-recess), .75 inch wall thickness (surface mount), brass hinge, custom handle, chromium-plated roller catch and strike, glass door panel.

SPECIFICATIONS:



Surface-Mount
Brighton Walnut Stain
Catalog Number 51002
Description 505-11 S

Catalog Number	TRIM STYLE AND PROJECTION	Inside Box Dimensions			Outside Trim Dimensions			Rough Opening			COMPLIES WITH ADA	EXTINGUISHER SIZES RECOMMENDED
		Height	Width	Depth	Height	Width	Depth	Height	Width	Depth		
		in.	in.	in.	in.	in.	in.	in.	in.	in.		
51001	SEMI-RECESS 3 1/8	24	9 1/2	5 5/8	28	13 1/2	N/A	25	10 1/2	4	YES	5 and 10 LB.
51002	SURFACE	24	9 1/2	6	26 7/8	11	8 3/16	----	----	----	N/A	5 and 10 LB.



Specifications:

Extinguisher Backboard

EXTRA VISIBILITY AT LOW COST!!!

THE CATO EXTINGUISHER BACKBOARD

Mount your extinguishers in the office or workplace to this attractive and highly visible backboard. The Cato Extinguisher Backboard makes it easier for the public to locate extinguishers quickly and provides a simple way for missing extinguishers to be reported.



FEATURES:

- “Extinguisher Missing” warning label
- Designated space to place contact information
- Illustrated “Fire” label
- UV resistant, injection-molded red polypropylene
- Pre-molded 1/4-inch mounting holes
- Rounded corners for maximum safety
- 5 and 10 lb. extinguisher sizes

Catalog #	Description	Dimension (WxH)
CBB-05	Red backboard for 5 and 2 1/2 lb. extinguishers	8 1/2" x 22 1/2"
CBB-10	Red backboard for 10 lb. extinguishers	10 1/2" x 27 3/4"



CATO Signs and Labels




CL401



CL403



CL413



CL415



CL416



CL416A



CL420



CL419



CL421



CL422

PULL TO OPEN

CL418



CL419



CL422



Specifications:

Extinguisher Cabinets



Warrior 95-5
Red Body/Clear Cover

THE WARRIOR FIRE EXTINGUISHER CABINET

FEATURES:

- Made in the U.S.A.
- Can not rust
- Will not fade
- No sharp corners
- No glass to shatter
- No paint to chip
- Pitched drainage
- Natural ventilation
- Fire retardant
- Dent-proof
- Lower freight cost
- Less storage space
- Less shipping damage
- Easily cleaned
- No padlock required
- High density injection molded
- All sizes in red or white
- Lower replacement costs

HIGHLIGHTS:

- Locking seal
- Two-piece construction
- No breaker bar
- Pulls up to remove cover
- Side labels included
- Brother of the Chief

SPECIFICATIONS:

Fire Extinguisher Cabinet, as manufactured by Cato, Inc. with cabinet body injection molded of linear, high density red or white virgin high-impact polystyrene of .110 wall thickness with ultra-violet inhibitors and high-impact crystal polystyrene .100 wall thickness one-piece cover.

Warrior bodies are available in red and white. Warrior covers are available in clear or red.



TS-101 Extinguisher Cabinet

TS-101 FIRE EXTINGUISHER CABINET

FEATURES:

- Clear door and security seal facility allows easy visual inspection
- Precision injection molded in polycarbonate for improved performance
- Universal capability will accommodate a variety of fire extinguishers (20 lbs. or less)
- Door seats designed to provide long-term weather protection
- Quick release door catches ensure rapid access
- Maintenance-free construction



DIMENSIONS:

30" x 11" x 8 1/4" (Height x Width x Depth)



Specifications:

The CATO CLASSIC

**THE CATO CLASSIC
PLASTIC EXTINGUISHER CABINET FOR SEMI-RECESS**



SPECIFICATIONS: Fire Extinguisher Cabinet, as manufactured by Cato, Inc., with body, bezel and door, injection molded of white virgin 2 Izod Co-Polymer Polypropylene of .15 wall thickness, virgin acrylic Plaskolite panel of .080 thickness, stainless steel hinge, chromium-plated door handle and roller catch.

Catalog Number
41001

Description
405-10 W

DIMENSIONS

TRIM STYLE AND PROJECTION	INSIDE BOX DIMENSIONS HxWxD	OUTSIDE TRIM DIMENSIONS HxWxD	ROUGH OPENINGS HxWxD	COMPLIES WITH ADA?	EXTINGUISHER SIZES RECOMMENDED
Semi-Recess 2 7/8	23 1/4 x 8 1/2 x 5 5/8	27 5/8 x 13 3/8	25 x 10 1/2 x 4	YES	5 or 10 lb.