

## Ordering Code Explanation for Ceco Doors

### Door Series

|    |                                                                               |
|----|-------------------------------------------------------------------------------|
| UP | Ultrador Series                                                               |
| IU | Imperial Series (polyurethane foam core, handed)                              |
| MS | Medallion (vertically stiffened, handed)                                      |
| RI | Regent (impregnated honeycomb core, handed)                                   |
| VU | Versador (polyurethane foam core, non-handed)                                 |
| CP | Commodity Polystyrene                                                         |
| LP | Legion Door                                                                   |
| OI | Omega Series (honeycomb core, non-handed)                                     |
| HE | Trio-E (vertically stiffened energy efficient door with polyurethane, handed) |

### Design

|      |                  |
|------|------------------|
| F    | Flush Door       |
| E601 | Embossed 6 Panel |

### Gauge & Material

|       |                             |
|-------|-----------------------------|
| 18GL4 | 18 Ga. A60 Galvanneal Steel |
| 18CRS | 18 Ga. cold rolled steel    |
| 16GL4 | 16 Ga. A60 galvanneal steel |
| 18GA  | 18 Gauge                    |
| 16GA  | 16 Gauge                    |
| 16CRS | 16 Ga. cold rolled steel    |

### Closer

|     |                                                                               |
|-----|-------------------------------------------------------------------------------|
| C1  | Standard Closer Blocking Reinforcement (14 gauge)                             |
| C2  | 2 Standard Closer Reinforcements Butted Together (14 gauge)                   |
| C4  | 4-5/8" high closer reinforcement                                              |
| PR1 | Standard Closer Reinforcement(14 gauge), Rim Exit Device (reinforce only)     |
| CH  | One standard reinforcement at top and one at the bottom of door at hinge side |
| CR  | Capped Reinforcement Channel - (Top Cap)                                      |
| CT  | Capped Top Channel - (Top Cap)                                                |
| PR  | Rim Panic Reinforcement                                                       |

### Bolt Type

|     |                     |
|-----|---------------------|
| AF2 | 1 Top / 12" Bottom  |
| MF8 | 24 Top / 12" Bottom |

**Lock Strike Panic Device Code**

|       |                                                                           |
|-------|---------------------------------------------------------------------------|
| LC1   | Govt. 161 x 2-3/4" Backset (2-1/8"Diameter Face Hole)                     |
| LL3   | Govt. 161 x 2-3/4" (69.850) b.s. (Corbin Russwin)                         |
| LL4   | Govt. 161 x 2-3/4 b.s. (sargent 10 Line)                                  |
| LM0   | Govt. 86 x Edge Only                                                      |
| LM7   | Govt. 86 x sectional trim w/special face preps                            |
| LMO   | Lock/Strike Prep: G86 Mortise Edge Only                                   |
| CBLC1 | Lock/Strike Prep: 161 Cylindrical                                         |
| PR1   | Rim Exit Device (reinforce only)                                          |
| PV3   | Surface Vert. Rod Exit Device (reinforce only)                            |
| 161   | Cylindrical lock - 2-1/8 STD Bore                                         |
| LM0   | Govt. 86 x edge only                                                      |
| LP0   | No Lock Prep (plain)                                                      |
| LPO   | No Lock Prep                                                              |
| P4    | 4-7/8 ANSI Deadlock Strike - No Lip                                       |
| SLA   | 4-7/8 ANSI lipped strike                                                  |
| NHP   | No butt hinge preps or cont. geared hinges without reinforcement required |

**Misc.**

|       |                                                                      |
|-------|----------------------------------------------------------------------|
| U06   | 3/8 Undercut                                                         |
| U12   | 3/4 Undercut                                                         |
| STC   | Steel Top Cap (screw applied)                                        |
| STH   | Steelcraft Hinge Spacing (hinge backset will be Steelcraft standard) |
| STL   | Steelcraft Lock Height                                               |
| DB    | 1.125 x 2.25 Edge, 2.75 b.s., 2.125 dia. Thru Door Deadlock          |
| 60PSF | +/- 60 PSF design load                                               |
| AW    | 3 Hour label also includes Positive Pressure                         |
| BW    | 1-1/2 Hour label also includes Positive Pressure                     |
| CUB   | Curries Both Hing & Lock Locations                                   |
| CUH   | Curries Hinge Spacing (hinge backset will be Curries standard)       |
| CUL   | Curries Lock Height                                                  |

**Handing**

|     |                    |
|-----|--------------------|
| NH  | Non-Handed         |
| LH  | Left Handed        |
| RH  | Right Handed       |
| LHR | Left Hand Reverse  |
| RHR | Right Hand Reverse |

**Nominal Size**

|       |                          |
|-------|--------------------------|
| 20 68 | 2'0" width x 6'8" height |
| 20 70 | 2'0" width x 7'0" height |
| 24 68 | 2'4" width x 6'8" height |
| 24 70 | 2'4" width x 7'0" height |
| 26 68 | 2'6" width x 6'8" height |
| 26 70 | 2'6" width x 7'0" height |
| 26 80 | 2'6" width x 8'0" height |
| 28 68 | 2'8" width x 6'8" height |
| 28 70 | 2'8" width x 7'0" height |
| 30 68 | 3'0" width x 6'8" height |
| 30 70 | 3'0" width x 7'0" height |
| 30 72 | 3'0" width x 7'2" height |
| 30 80 | 3'0" width x 8'0" height |
| 30 90 | 3'0" width x 9'0" height |
| 34 68 | 3'4" width x 6'8" height |
| 34 70 | 3'4" width x 7'0" height |
| 36 68 | 3'6" width x 6'8" height |
| 36 70 | 3'6" width x 7'0" height |
| 36 80 | 3'6" width x 8'0" height |
| 38 68 | 3'8" width x 6'8" height |
| 38 70 | 3'8" width x 7'0" height |
| 40 68 | 4'0" width x 6'8" height |
| 40 70 | 4'0" width x 7'0" height |
| 40 80 | 4'0" width x 8'0" height |