

MATERIAL SAFETY DATA SHEET 3M
DATA SHEET 3M Center
 St. Paul, Minnesota
 55144-1000
 1-800-364-3577 or (651) 737-6501 (24 hours)

Copyright, 2001, Minnesota Mining and Manufacturing Company.
All rights reserved. Copying and/or downloading of this
information for the purpose of properly utilizing 3M products
is allowed provided that:
1) the information is copied in full with no changes unless

- 1) the information is copied in full with no changes unless prior agreement is obtained from 3M, and
- 2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

DIVISION: ENGINEERED ADHESIVES

TRADE NAME:

3M Citrus Base Industrial Cleaner (Aerosol)

ID NUMBER/U.P.C.:

62-4615-1730-2 - - - 62-4615-4930-5 00-21200-76394-6
62-4615-4935-4 - - -

ISSUED: May 29, 2001

SUPERSEDES: April 05, 1999

DOCUMENT: 11-0029-6

1. INGREDIENT	C.A.S. NO.	PERCENT
D-LIMONENE.....	5989-27-5	70.0 - 80.0
PROPANE (AS PROPELLANT).....	74-98-6	10.0 - 20.0
NONIONIC SURFACTANT MIX - N.J. TRADE		
SECRET (T.S.) REGISTRY NO. 800927-5000P	TradeSecret	7.0 - 13.0

The components of this product are in compliance with the chemical notification requirements of TSCA.

2. PHYSICAL DATA

BOILING POINT:..... Compressed gas
VAPOR PRESSURE:..... Compressed gas
VAPOR DENSITY:..... N/A
EVAPORATION RATE:..... N/A
SOLUBILITY IN WATER:..... slight
SPECIFIC GRAVITY:..... 0.784 Water=1
PERCENT VOLATILE:..... ca. 91 % by wt
pH:..... N/A
VISCOSITY:..... N/A
MELTING POINT:..... N/D

APPEARANCE AND ODOR:

liquid in aerosol container, clear, pale yellow, sweet odor

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

3. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: -50.00 F
FLAMMABLE LIMITS - LEL: N/A
FLAMMABLE LIMITS - UEL: Flam.Gas
AUTOIGNITION TEMPERATURE: N/D

EXTINGUISHING MEDIA:

Water spray, Carbon dioxide, Dry chemical, Foam

SPECIAL FIRE FIGHTING PROCEDURES:

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head. Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Closed containers exposed to heat from fire may build pressure and explode.

NFPA HAZARD CODES: HEALTH: 2 FIRE: 4 REACTIVITY: 1 AEROSOL STORAGE: 2
UNUSUAL REACTION HAZARD: none

4. REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY - MATERIALS/CONDITIONS TO AVOID:
Heat.

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide and Carbon Dioxide, Aldehydes, Ketones, Hydrocarbons.

5. ENVIRONMENTAL INFORMATION

SPILL RESPONSE:

Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Ventilate area. Extinguish all ignition sources. Cover with absorbent material. Collect using non-sparking tools. Place in a U.S. DOT-approved container.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

5. ENVIRONMENTAL INFORMATION (continued)

RECOMMENDED DISPOSAL:

Incinerate in a permitted hazardous waste incinerator in the presence of a combustible material. Facility must be capable of handling aerosol cans. Dispose of empty cans in a sanitary landfill. Dispose of completely absorbed waste product in a facility permitted to accept chemical wastes.

RECYCLE EMPTY AEROSOL CONTAINERS WHERE AVAILABLE.

ENVIRONMENTAL DATA:

Not determined.

REGULATORY INFORMATION:

Volatile Organic Compounds: ca. 91 % calculated per SCAQMD rule 443.1.
VOC Less H₂O & Exempt Solvents: ca. 740 gms/liter tested per EPA method 24 and SCAQMD305.

Since regulations vary, consult applicable regulations or authorities before disposal. U.S. EPA Hazardous Waste Number = D001 (Ignitable)

EPCRA HAZARD CLASS:

FIRE HAZARD: Yes PRESSURE: Yes REACTIVITY: No ACUTE: Yes CHRONIC: Yes

6. SUGGESTED FIRST AID

EYE CONTACT:

Immediately flush eyes with large amounts of water. Get immediate medical attention.

SKIN CONTACT:

Flush skin with large amounts of water. If irritation persists, get medical attention.

INHALATION:

Remove person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, get immediate medical attention.

IF SWALLOWED:

Do not induce vomiting. Drink two glasses of water. Call a physician.

7. PRECAUTIONARY INFORMATION

EYE PROTECTION:

Avoid eye contact with vapor, spray, or mist. Wear safety glasses with side shields.

SKIN PROTECTION:

Avoid prolonged or repeated skin contact.

RECOMMENDED VENTILATION:

Do not use in a confined area or areas with little or no air movement. If exhaust ventilation is not adequate, use appropriate respiratory protection. Provide ventilation adequate to control vapor concentrations below recommended exposure limits and/or control spray or mist.

RESPIRATORY PROTECTION:

Avoid breathing of vapors, mists or spray.

PREVENTION OF ACCIDENTAL INGESTION:

Do not ingest.

RECOMMENDED STORAGE:

Store at temperatures below 120 degrees F (49 degrees C). Store out of direct sunlight. Keep out of the reach of children.

FIRE AND EXPLOSION AVOIDANCE:

Aerosol container contains flammable gas under pressure. Keep away from heat, sparks, open flame, and other sources of ignition. Extremely flammable liquid and vapor. Do not pierce or burn container, even after use. No smoking while handling this material.

EXPOSURE LIMITS

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
D-LIMONENE.....	30	PPM	TWA	AIHA	
PROPANE (AS PROPELLANT).....	1000	PPM	TWA	OSHA	
PROPANE (AS PROPELLANT).....	2500	PPM	TWA	ACGIH	
NONIONIC SURFACTANT MIX - N.J.					
TRADE SECRET (T.S.) REGISTRY NO.					
800927-5000P.....	NONE	NONE	NONE	NONE	NONE

* SKIN NOTATION: Listed substances indicated with 'Y' under SKIN refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

SOURCE OF EXPOSURE LIMIT DATA:

- ACGIH: American Conference of Governmental Industrial Hygienists

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

EXPOSURE LIMITS (continued)

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
<hr/>					
- AIHA: American Industrial Hygiene Assoc. Workplace Environmental Exposure Level Guideline					
- OSHA: Occupational Safety and Health Administration					
- NONE: None Established					

8. HEALTH HAZARD DATA

EYE CONTACT:

Moderate Eye Irritation: signs/symptoms can include redness, swelling, pain, tearing, and hazy vision.

SKIN CONTACT:

Moderate Skin Irritation (after prolonged or repeated contact):
signs/symptoms can include redness, swelling, itching, and dryness.

INHALATION:

Intentional concentration and inhalation may be harmful or fatal.

Central Nervous System Depression: signs/symptoms can include headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.

Irritation (upper respiratory): signs/symptoms can include soreness of the nose and throat, coughing and sneezing.

IF SWALLOWED:

Ingestion is not a likely route of exposure to this product.

WHILE THE FOLLOWING EFFECTS ARE ASSOCIATED WITH ONE OR MORE OF THE INDIVIDUAL INGREDIENTS IN THIS PRODUCT AND ARE REQUIRED TO BE INCLUDED ON THE MSDS BY THE U.S. OSHA HAZARD COMMUNICATION STANDARD, THEY ARE NOT EXPECTED EFFECTS DURING FORESEEABLE USE OF THIS PRODUCT.

Irritation of Gastrointestinal Tissues: signs/symptoms can include pain, vomiting, abdominal tenderness, nausea, blood in vomitus, and blood in feces.

SECTION CHANGE DATES

HEADING SECTION CHANGED SINCE April 05, 1999 ISSUE

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.