

Product Data Sheet

Fire Alarm Nonshielded Nonplenum

Product Description

Power limited fire alarm and communications cable for riser or nonriser applications. Fire alarm, smoke detectors, signaling and fire-protective circuits. XX in part number denotes color; call your local sales representative for specific requirements.

Specifications

- CONDUCTOR: Solid bare copper
- INSULATION: PVC
- JACKET: PVC with rip cord
- STANDARDS: NEC FPLR, UL Listed
- TEMPERATURE: 75°C

Tech. Info & Standards

PVC

Solid conductor

FPLR, UL Listed

Part No.	Conductor Size AWG	No. of Conductors	Insulation Thickness (in.)	Jacket Thickness (in.)	Nom. O.D. (in.)	Approx. Wt. lb./1,000 ft.
FA-1202C-1-1N-XX	12	2	0.012	0.015	0.264	62
FA-1204C-1-1N-XX	12	4	0.012	0.015	0.258	80
FA-1402C-1-1N-XX	14	2	0.010	0.015	0.212	40
FA-1404C-1-1N-XX	14	4	0.010	0.015	0.252	73
FA-1602C-1-1N-XX	16	2	0.010	0.015	0.183	28
FA-1604C-1-1N-XX	16	4	0.010	0.015	0.216	49
FA-1802C-1-1N-XX	18	2	0.010	0.015	0.156	19
FA-1804C-1-1N-XX	18	4	0.010	0.015	0.181	33
FA-1806C-1-1N-XX	18	6	0.010	0.015	0.223	49
FA-2204C-1-1N-XX	22	4	0.010	0.015	0.122	15