



eFlow104NX8

### Overview

eFlow104NX8 is a power supply/charger that converts a 120VAC 60Hz input into eight (8) fuse protected 24VDC outputs with a total of 10 amps max. The unit includes a Class 2 rated unswitched aux. output. It also offers a suite of features that includes fire alarm disconnect, over voltage protection, and low power disconnect which prevents deep discharge of stand-by batteries.



### Specifications

#### Input:

- 120VAC, 60Hz, 4.5 amp.
- Input fuse: 5A/250V.

#### Output:

- Eight (8) fuse protected outputs.
- Outputs are rated @ 2.5 amp.
- 24VDC @ 10.0 amp supply current.
- Auxiliary Power-Limited output rated @ 1 amp (unswitched).
- Over Voltage Protection.

#### Battery Backup:

- Built-in charger for sealed lead acid or gel type batteries.
- Maximum charge current 1.54 amp.
- Automatic switch over to stand-by battery when AC fails. Transfer to stand-by battery power is instantaneous with no interruption.

#### Supervision:

- AC fail supervision (form "C" contacts).
- Battery fail & presence supervision (form "C" contacts).
- Low power shutdown. Shuts down DC output terminals if battery voltage drops below 70-75% (depending on the power supply). Prevents deep battery discharge.

#### Fire Alarm Disconnect:

- Supervised Fire Alarm disconnect (latching or non-latching) 10K EOL resistor. Operates on a normally open (NO) or normally closed (NC) trigger.

#### Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.: 124.85 BTU/Hr.
- System AC input VA requirement: 540VA.

#### Visual Indicators:

- Green AC Power LED indicates 120VAC present.
- AC input, DC output and Battery LED indicators.

#### Additional Features:

- Short circuit and overload protection.
- Unit is complete with power supply, enclosure, battery leads and cam lock.

#### Mechanical:

- Enclosure Dimensions (H x W x D approx.): 15.5" x 12" x 4.5" (393.7mm x 304.8mm x 114.3mm)
  - Accommodates up to two (2) 12VDC/12AH batteries.
- Product weight (approx.): 11.85 lbs. (5.38 kg).
- Shipping weight (approx.): 13.15 lbs. (5.96 kg).

### Agency Approvals



- |         |   |
|---------|---|
| UL 294  | UL Listed for Access Control System Units.                          |
| UL 603  | UL Listed for Power Supplies for Use with Burglar-Alarms Systems.   |
| UL 1481 | UL Listed for Power Supplies for Fire Protective Signaling Systems. |



ULC-S318-96 - Power Supplies for Burglar Alarm Systems. Also suitable for Access Control.



CE - European Conformity

**Enclosure Dimensions (H x W x D approximate):**  
**15.5" x 12" x 4.5" (393.7mm x 304.8mm x 114.3mm)**

