



Illustra Flex IP Mini-Domes

Affordable and Versatile Indoor and Outdoor

Features That Make a Difference:

- 1MP and 3MP resolution for true HD quality images
- Bandwidth and storage friendly
- True Day/Night (TDN) functionality for a true color image
- 3D noise reduction for sharper images and lower bandwidth use in low light
- IR illuminators for clear images in low light conditions (Outdoor only)
- Motion detection for instant alerts of intruders
- IP66-rated enclosure to protect against dust and water damage (Outdoor only)
- A variety of mounting options for quick and easy installation
- ONVIF 2.2 profile S compliant



Indoor



Outdoor

The versatile Illustra Flex Mini-Dome, Indoor or Outdoor, is a True Day/Night network camera that provides 1MP and 3MP full HD resolution for high quality images. H.264 and MJPEG video compression provides excellent image clarity, and efficient bandwidth and video storage.

With a small, aesthetically pleasing design, the affordably priced Illustra Flex Mini-Dome offers an effective solution for retail stores, K-12 schools, small bank branches and small to medium size offices with a tight budget and a variety of surveillance needs. With a variety of mounting options making it easy to install, these cameras can be strategically placed to blend into a variety of interior locations such as the cash register terminal at a retail store, the lobby/corridor of an elementary school or inside a 24 hour ATM vestibule.

Featuring built-in IR illuminators, the outdoor Illustra Flex Mini-Dome produces clear images at an effective distance up to 49 feet in a variety of low light conditions. The outdoor camera also comes with a vandal-resistant housing to protect the camera against external impacts that might occur if an intruder was attempting to take the camera out of operation. With an IP66-rated enclosure, this outdoor mini-dome is ideal in situations where dust or water could damage the camera – a loading dock, parking lot or off-site warehouse.

Specifications

Operational	
Video Compression.....	H.264/MJPEG
Max Frame Rate	
Illustra Flex 600.....	720p @ 30ips
Illustra Flex 800.....	3MP @ 15ips 1080p @ 30ips
ONVIF-Compliant.....	Yes
Resolutions	
Illustra Flex 600.....	720p (1280x720) SVGA (800x600) D1 (720x480) VGA (640x480) CIF (352x240)
Illustra Flex 800.....	3.1MP QXGA (2048x1536) 3MP (2304x1296) 1080p (1920x1080) SXGA (1280x960) 720p (1280x720) SVGA (800x600) D1 (720x480) 4CIF (704x480) VGA (640x480) CIF (352x240)
Imager.....	1/3" CMOS
Day/Night.....	Mechanical ICR
Minimum Illumination	
Indoor.....	0.3 lux @ F1.2 color; 0.1 lux b/w
Outdoor.....	0.3 lux at F1.2 color; 0.00 lux in IR Illuminator mode
IR Illuminator (Outdoor)	Effective distance is 15m/49ft, IR wavelength 850nm
Shutter Speed.....	1/7.5~1/8000 sec
Backlight Compensation.....	Off/On (6 selectable areas)
Lens Focal Length	3-9mm F1.2 varifocal lens
Field of View (H/V).....	Wide Angle: 98°/53° Telephoto: 33°/19°
White Balance.....	ATW (2500K~8000K)/Manual
Alarms	Motion detection
Alarm Input/Output	1/1
Audio Input/Output	1/1
Audio Format	G.711-Alaw/G.711-Ulaw
Video Output.....	1
Video Stream.....	Triple
Wide Dynamic Range.....	Digital WDR
Digital Noise Reduction.....	3D
Privacy Zones	Yes, 4
Menu Languages.....	Arabic, Chinese (Simplified), Chinese (Traditional), Czech, Danish, Dutch, English (default), Finnish, French, German, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish
Network	
Ethernet	RJ-45 connector
Supported Protocols.....	IPv4, HTTP, HTTPS, TCP, RTSP/RTCP/RTP, ICMP, UDP, IGMP, DNS, DHCP, ARP, NTP, SMTP
Configuration Management	
Web Browsing	
Requirements	Internet Explorer 8.0 or above
Security.....	Multiple user access levels with password protection
Onboard Storage	
Card Support.....	SDHC/SDXC
Electrical	
Power	
Indoor.....	12V DC, 24V AC, PoE 802.3af Class 0
Outdoor.....	24V AC, PoE 802.3af Class 0
Power Consumption	
Illustra Flex 600.....	Indoor: 6.8W; Outdoor 10.3W
Illustra Flex 800.....	Indoor: 7W; Outdoor 10.5W
Physical	
Dimension (DxH)	
Indoor.....	125 x 106 mm (4.92 x 4.17 in)
Outdoor.....	147 x 140.5 mm (5.79 x 5.53 in)
Weight	
Indoor.....	0.8 kg (1.76 lbs)
Outdoor.....	1.9 kg (4.18 lbs)
Housing Material	
Indoor.....	Polycarbonate & ABS
Outdoor.....	ADC12
Housing Color	
Indoor.....	Pantone Cool Gray 1C
Outdoor.....	Light Gray RAL 7035
Operating Temperature	
Indoor.....	-10°C to 50°C (14°F to 122°F)
Outdoor.....	24V AC power: -40°C to 50°C (-40°F to 122°F) PoE power: -10°C to 50°C (14°F to 122°F)
Operating Humidity	0% to 90%, non-condensing
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Regulatory	
Emissions	FCC Class A; CE Class A
IP Rating	IP66 (Outdoor only)

Ordering Information

Model Numbers	Description
ADCI600F-D111	Illustra Flex 600 Indoor Min-Dome, 1MP, varifocal 3-9mm lens
ADCI600F-D021	Illustra Flex 600 Outdoor Mini-Dome, 1MP, varifocal 3-9mm lens, IR
ADCI800F-D111	Illustra Flex 800 Indoor Mini-Dome, 3MP, varifocal 3-9mm lens
ADCI800F-D021	Illustra Flex 800 Outdoor Mini-Dome, 3MP, varifocal 3-9mm lens, IR

* Unless otherwise noted, all specifications are the same for both Illustra Flex 600 and Illustra Flex 800 Indoor and Outdoor models

Related Products



exacqVision
NVR

Approvals



www.exacq.com/illustra