

Access Control Credentials

We offer a variety of access control credentials—from key fobs to access control cards. Choose from printable, durable, vertically or horizontally oriented cards, with various read ranges and numbering capabilities from some of the top brands in access control.

INFINIAS CLAMSHELL ACCESS CONTROL PROXIMITY CARD S-ACC-CLM

- ► Thin, durable card ts easily inside a wallet, pocket or purse
- Printable
- Consistent read range
- White card with textured surface
- Convenient card slot for attaching lanyards and badge clips



INFINIAS PVC ACCESS CONTROL PROXIMITY CARD

S-ACC-PVC

- Provides convenient and secure access control at your facility
- Printable
- Consistent read range
- ► Glossy graphics quality surface
- Same size and thickness of a standard credit card
- Vertical or horizontal slot punch



INFINIAS ACCESS CONTROL SMART CARD

S-ACC-3020

- Features proprietary smart card technology for secure communications
- For legacy IDC smart card installations only
- Proprietary smart card technology
- ▶ 1.0" to 2.0" read range
- Printable
- CR-80 format
- 2K memory



 $\label{thm:choosing:call} \textit{Questions? Need help choosing? Call us today to speak with an access control technician.}$





HID ISOPROX II ACCESS CARD WITH SPECIAL CARD NUMBERING

A-PVC-1000-SP

- Printable
- ▶ 125 kHz transmit frequency
- Sequential matching internal/external card numbering
- ▶ 2.5" to 20" read range
- Vertical or horizontal slot punch options



HID PROXCARD II ACCESS CONTROL CLAMSHELL WITH SPECIAL CARD NUMBERING

A-ACC-1000-SP

- Supports up to 26 bits
- ▶ 125 kHz transmit frequency
- O ers over 137 billion unique codes
- Consistent read range
- Resistant to cracking and breaking
- Sequential matching internal/external card numbering (ink jet printed)
- White with gloss nish front
- Vertical slot punch for portrait orientation




HID ISOPROX II ACCESS CARD

A-PVC-1000

- Printable
- ▶ 125 kHz transmit frequency
- Optimized graphics quality surface for enhanced photo ID printing with direct image printers
- ▶ 2.5" to 20" read range
- Same size/thickness as standard credit card
- Vertical or horizontal slot punch options









HID MULTI-TECHNOLOGY DUOPROX II ACCESS CARD

A-PVC-1100

- Printable
- Magnetic strip and proximity technology
- ▶ 125 kHz transmit frequency
- Graphics quality surface for use with direct image printers
- ▶ 2.5" to 20" read range
- > Same size/thickness as standard credit card
- Vertical or horizontal slot punch options



HID PROXKEY-II WIEGAND ACCESS CONTROL KEY FOB

A-AKT-1000

- ► RF programmable
- Supports up to 26 bits
- ▶ 125 kHz transmit frequency
- O ers over 137 billion unique codes
- Gray with standard HID logo
- ▶ Easily ts on key ring for convenient access
- Provides universal compatibility with HID proximity readers
- External numbering provides easy identication and control



HID PROXCARD II ACCESS CONTROL CLAMSHELL

A-ACC-1000

- Supports up to 26 bits
- ▶ 125 kHz transmit frequency
- O ers over 137 billion unique codes
- Consistent read range
- Resistant to cracking and breaking
- Sequential matching internal/external card numbering (ink jet printed)
- White with gloss nish front
- Vertical slot punch for portrait orientation



Questions? Need help choosing? Call us today to speak with an access control technician.





Access Control Credential Comparison Chart



















	1		The state of the s						
Product Name	infinias Clamshell Access Control Proximity Card	infinias PVC Access Control Proximity Card	infinias Access Control Smart Card*	HID ISOProx II Access Card with Special Card Numbering	HID ProxCard II Access Control Clamshell with Special Card Numbering	HID ISOProx II Access Card	HID Multi- technology DuoProx II Access Card	HID ProxKey- II Wiegand Access Control Key Fob	HID ProxCard II Access Control Clamshell
SKU	S-ACC-CLM	S-ACC-PVC	S-ACC-3020	A-PVC-1000- SP	A-ACC-1000- SP	A-PVC-1000	A-PVC-1100	A-AKT-1000	A-ACC-1000
Read Range	2.5" to 24"	2.5" to 20"	1.0" to 2.0"	2.5" to 20"	3.0" to 29"	2.5" to 20"	2.5" to 20"	1.5" to 17.0"	3.0" to 29"
Credential Type	Card	Card	Card	Card	Card	Card	Card	Key Fob	Card
Slot Punch	Vertical (Standard)	Horizontal or Vertical Optional	Horizontal or Vertical Optional	Horizontal or Vertical Optional	Vertical (Standard)	Horizontal or Vertical Optional	Horizontal or Vertical Optional	Key Ring Hole	Vertical (Standard)
Printable	Yes	Yes	Yes	Yes	No	Yes	Yes	No	No
Card Options	None	None	None	External card numbering (inkjet or laser engraving) Custom artwork (text or graphics)	External card numbering (inkjet only; no laser engraving) Custom artwork (text or graphics)	None	External card numbering (inkjet or laser engraving) Custom artwork (text or graphics) A variety of magnetic stripe types	None	None
Construc- tion	Strong, exible and resistant to cracking and breaking	Thin, exible polyvinyl chloride (PVC) laminate	Thin, exible polyvinyl chloride (PVC) laminate	Thin, exible polyvinyl chloride (PVC) laminate	Strong, exible and resistant to cracking and breaking	Thin, exible polyvinyl chloride (PVC) laminate	Thin, exible polyvinyl chloride (PVC) laminate	Ultrasonically welded, ABS shell	Strong, exible and resistant to cracking and breaking
Dimensions (H" x W" x D")	2.135 x 3.385 x 0.075	2.125 x 3.375 x 0.033	2.125 x 3.375 x 0.033	2.125 x 3.375 x 0.033	2.135 x 3.385 x 0.075	2.125 x 3.375 x 0.033	2.125 x 3.375 x 0.033	1.90 x 0.900 x 0.550	2.135 x 3.385 x 0.075
Operating Tempera- ture (F)	-50° ~ 160°	-50° ~ 160°	-50° ~ 160°	-50° ~ 160°	-50° ~ 160°	-50° ~ 160°	-50° ~ 160°	-50° ~ 160°	-50° ~ 160°
Color	White	White	White	White	White	White	White	Gray	White
Weight (Oz	0.24	0.24	0.24	0.24	0.24	0.24	0.24	0.26	0.24
Frequency	125 kHz	125 kHz	13 mHz	125 kHz	125 kHz	125 kHz	125 kHz	125 kHz	125 kHz

^{*} Designed to run on legacy intelli-m installations only

