

Overview

The IFS Fiberpak™ FP1500WDM fiber optic transmission kit includes everything you need to transmit a CCTV signal with one-way PTZ control data on one multimode optical fiber. The kit includes a transmitter and receiver that are designed to be universally compatible with major CCTV camera manufacturers and support RS-232 and RS-422 data interfaces and all major data protocols. In addition the kit includes wall mount AC transformers for both transmitter and receiver as well as a complete installation and operations manual. FiberPak™ Videolinks Plug-and-play design and included accessories make selecting the right fiber optic modules for your installation easy.

Application Examples

Compatible with:

- Kalatel® Video and One-Way RS-422 Data
- Pelco® Video and One-Way Type "P" Data
- Pelco® Video and One-Way Type "D" Data
- Sensormatic AD® Video and One-Way Manchester Data
- Vicon® Video and One-Way Modupulse Data


FP1500WDM Fiberpak™ Video Link IFS Video with One-Way Data Transmission Kit

Standard Features

- AM Transmission
- Automatic Resettable Fuses on all Power Lines
- Power Supplies and Installation Manuals Included
- Supports RS-232 or RS-422 Data Interfaces
- Transparent to Data Encoding/Compatible with Major CCTV Camera Manufacturers
- Full Range Automatic Gain Control (AGC)
- No In-field Electrical or Optical Adjustments Required
- NTCIP Compatible
- Full Color Compatibility
- Tested and Certified by an Independent Testing Laboratory for Full Compliance with the Environmental Requirements (Ambient Operating Temperature, Mechanical Shock, Vibration, Humidity with Condensation, High-Line/Low-Line Voltage Conditions and Transient Voltage Protection) of NEMA TS-1/TS-2 and the Caltrans Specification for Traffic Signal Control Equipment.
- Power, Video Presence In, Data Out, and AGC Status Indicating LED's to Monitor System Performance
- Integrated WDM for Greater Product Reliability
- NTSC, PAL, SECAM Compatible
- Distances up to 2.5 miles (4 km) without Repeaters
- Comprehensive Lifetime Warranty

Video with One-Way Data Transmission

Transmit a CCTV signal with
one-way PTZ control data on
one multimode optical fiber.



GE Security

North America
T 888-GE-SECURITY
888-437-3287
F 503-691-7566
E sales@ifs.com

Asia
T 852-2907-8108
F 852-2142-5063

Australia and New Zealand
T 613-9239-1200
F 613-9239-1299

Europe
T 44-113-238-1668
F 44-113-253-8121


Latin America
T 305-593-4301
F 305-593-4300

gesecurity.com/ifs

Specifications subject to
change without notice

© 2008 General Electric Company
All Rights Reserved

Agency compliance



Made in the USA

Complies with FDA Performance
Standard for Laser Products, Title 21,
Code of Federal Regulations, Subchapter J

Specifications

Video

Video Input: 1 volt pk-pk (75 ohms)
Bandwidth: 5 Hz - 10 MHz**
Differential Gain: <5%
Differential Phase: <5°
Tilt: <1%
Signal-to-Noise Ratio (SNR): >55 dB @ 10 dB Attn.

Data

Data Interface: RS-232, RS-422
Data Format: NRZ, NRZI, Manchester, Bi-phase
Data Rate: DC-100 Kbps (NRZ)

Sync

Output Voltage: 4 volt negative pulse
Impedance: 75 ohms

Wavelength

850/1310 nm, Multimode

Number Of Fibers

VT1500: 2 VT1500WDM: 1

Connectors

Optical: ST
Power and Data: Terminal Block with Screw Clamps
Video and Sync: BNC (Gold Plated Center-Pin)

Electrical & Mechanical


Power:
Transmitter: 24 VAC C.T. @ 200 mA
Receiver: 12 VDC @ 500 mA
Current Protection: Automatic Resettable Solid-State Current Limiters
Circuit Board: Meets IPC Standard
Size (in./cm.) (LxWxH): 7.0 x 4.9 x 1.0 in., 17.8 x 12.5 x 2.5 cm
Surface Mount:
Shipping Weight: < 2 lbs./0.9 kg

Environmental

MTBF: > 100,000 hours
Operating Temp: -40° C to +74° C
Storage Temp: -40° C to +85° C
Relative Humidity: 0% to 95% (non-condensing)†

†May be extended to condensation conditions by adding suffix '-C' to model number for conformal coating.

System Design



Ordering Information

	Part Number	Description	Fibers Required	Optical Pwr. Budget	Max. Distance*
Multimode 62.5/125µm**	FP1500WDM	FiberPak™ Video Transmitter (850/1310 nm) FiberPak™ Video Receiver (1310/850 nm)	1	14 dB	2.5 mile (4 km)
Accessories♦	PS-12VDC 12 Volt DC Plug-in Power Supply (Included) PS-12VDC-230 12 Volt DC Plug-in Power Supply, 230 VAC Input (Included if specified at time of order)				

*Optical transmission distance is limited to optical loss of the fiber and any additional loss introduced by connectors, splices and patch panels.
Distance can also be limited by fiber bandwidth. **For 50/125 Fiber, subtract 4 dB from Optical Power Budget. ♦All accessories are third party manufactured.



imagination at work