

# 114A00-1



**UPC Code:** 87225700714

**Country of Origin:** Please Contact Customer Service

## Brand Features

Omni-Bus is a distributed control system for lights, shades, fans, shutters, pumps, and more. Utilizing the worldwide DIN rail standard for mounting, Omni-Bus controls CFL, LED, electronic low voltage, Halogen, and incandescent lighting. Output devices are rated for 110/220/240V 50-60Hz markets unless otherwise noted. All wall stations are 24VDC and below. Modular Omni-Bus components can be located where needed to save wiring and installation costs. Elegant, multi-button programmable wall stations eliminate the expense of in-wall high voltage wiring to multi-way switches.

## Item Description

Omni-Bus 6-Channel Universal Switch Interface Modules

## Features and Benefits

- Used to accommodate any shape and style momentary contact switch
- Connect up to six momentary contact switches to the bus and operate them as if it were an Omni-Bus Wall Station, with all of the same functionality
- Also supports up to six two-lead bi-color or single color LED indicators, one for each switch
- Features control for on/off, dimming, brightening, and scene control, configurable operating modes, and can be linked to a Leviton Omni or Lumina controller
- Bus side supply voltage: 15-24VDC (via bus network cable)
- Bus side supply current: 40mA maximum (without 12VDC output consumption)
- Auxiliary Output voltage: 12VDC @ 100mA max
- Ambient Temperature: 0 – 40 °C (32 – 104 °F)
- Ingress Protection: IP20
- Dimensions: 46mm x 50mm x 21mm
- LED drive current: 5mA maximum per LED
- Switch input maximum contact resistance: 1kohm
- Maximum recommended switch input cable length:
  - 10m (33 feet)
- All modules are CE, FCC, UL (ETL), SASO, and C-Tick approved

## SPECIFICATION SUBMITTAL

|   |  |
|---|--|
| JOB NAME:<br><input type="text"/><br>JOB NUMBER: <input type="text"/> | CATALOG NUMBERS:<br><input type="text"/> <input type="text"/><br><input type="text"/> <input type="text"/> |
|---|--|

**Leviton Manufacturing Co., Inc.**

201 North Service Road, Melville, NY 11747

Telephone: 1-800-323-8920 · FAX: 1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): 1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: 1-800-469-7890 ·

FAX: 1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2012-2015 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to: [www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

