

SIP 3020
SIP 4010
SIP 404
SIP 3020/5
SIP 4010/5
SIP 404/5
SIP 3020WF
SIP4010WF
SIP404WF
iSeries SIP 3020WFi
iSeries SIP4010WFi
iSeries SIP404WFi
SIP 3020CAM
SIP 5030
SIP 100
REDS CAN RLS 3060SH
REDNET

Quality detection system for video surveillance
REDWALL[®]
Unrivalled performance



Intelligent PIR Detection System for CCTV Applications

Detects ambient temperature and illuminance for automatic sensitivity management

Advanced detection algorithm

Detection logic selector

Adjustable alarm interval time

Wireless Ready version available (WF Series)

Anti-Vandalism Functions

Anti-rotation function with 3-axis accelerometer

Anti-masking function with photo-beam

Reinforced polycarbonate housing

Max. 13ft. (4m) installation height



SIP-3020WF (3020WFi), SIP-4010WF (4010WFi), SIP-404WF (404WFi)

FEATURES

- Wireless Ready, Battery Operated version
- Works with most manufacturer's wireless systems

The SIP-3020WF, SIP-4010WF, and SIP-404WF are designed to provide a reliable, wireless solution for your business. They are easy to install and use, and they provide a clear, bright display that is easy to read. They are also designed to be durable and long-lasting, so you can rely on them for years to come.

The SIP-3020WF, SIP-4010WF, and SIP-404WF are designed to provide a reliable, wireless solution for your business. They are easy to install and use, and they provide a clear, bright display that is easy to read. They are also designed to be durable and long-lasting, so you can rely on them for years to come.

Models	SIP-3020WF, SIP-4010WF, SIP-404WF SIP-3020WFi, SIP-4010WFi, SIP-404WFi (Inovonics Transmitter & Battery included in WFi)
Dimensions	SIP-3020: 13.0 x 3.3 x 1.0 in. SIP-4010: 13.0 x 3.3 x 1.0 in. SIP-404: 13.0 x 3.3 x 1.0 in.
Weight	SIP-3020: 0.5 lb. SIP-4010: 0.5 lb. SIP-404: 0.5 lb.
Power	1.5W (SIP-3020WF, SIP-4010WF, SIP-404WF) 1.5W (SIP-3020WFi, SIP-4010WFi, SIP-404WFi)
Frequency	433.92 MHz (SIP-3020WF, SIP-4010WF, SIP-404WF) 433.92 MHz (SIP-3020WFi, SIP-4010WFi, SIP-404WFi)
Range	1000 ft. (SIP-3020WF, SIP-4010WF, SIP-404WF) 1000 ft. (SIP-3020WFi, SIP-4010WFi, SIP-404WFi)
Display	1.5" (SIP-3020WF, SIP-4010WF, SIP-404WF) 1.5" (SIP-3020WFi, SIP-4010WFi, SIP-404WFi)
Buttons	1 (SIP-3020WF, SIP-4010WF, SIP-404WF) 1 (SIP-3020WFi, SIP-4010WFi, SIP-404WFi)
Material	Plastic (SIP-3020WF, SIP-4010WF, SIP-404WF) Plastic (SIP-3020WFi, SIP-4010WFi, SIP-404WFi)
Color	Black (SIP-3020WF, SIP-4010WF, SIP-404WF) Black (SIP-3020WFi, SIP-4010WFi, SIP-404WFi)
Finish	Matte (SIP-3020WF, SIP-4010WF, SIP-404WF) Matte (SIP-3020WFi, SIP-4010WFi, SIP-404WFi)
Accessories	Transmitter (SIP-3020WF, SIP-4010WF, SIP-404WF) Transmitter (SIP-3020WFi, SIP-4010WFi, SIP-404WFi)
Warranty	1 Year (SIP-3020WF, SIP-4010WF, SIP-404WF) 1 Year (SIP-3020WFi, SIP-4010WFi, SIP-404WFi)

SIP-100, SIP-5000

The SIP-100 and SIP-5000 are designed to provide a reliable, wireless solution for your business. They are easy to install and use, and they provide a clear, bright display that is easy to read. They are also designed to be durable and long-lasting, so you can rely on them for years to come.

The SIP-100 and SIP-5000 are designed to provide a reliable, wireless solution for your business. They are easy to install and use, and they provide a clear, bright display that is easy to read. They are also designed to be durable and long-lasting, so you can rely on them for years to come.

Dimensions	SIP-100: 13.0 x 3.3 x 1.0 in. SIP-5000: 13.0 x 3.3 x 1.0 in.
Weight	SIP-100: 0.5 lb. SIP-5000: 0.5 lb.
Power	1.5W (SIP-100, SIP-5000)
Frequency	433.92 MHz (SIP-100, SIP-5000)
Range	1000 ft. (SIP-100, SIP-5000)
Display	1.5" (SIP-100, SIP-5000)
Buttons	1 (SIP-100, SIP-5000)
Material	Plastic (SIP-100, SIP-5000)
Color	Black (SIP-100, SIP-5000)
Finish	Matte (SIP-100, SIP-5000)
Accessories	Transmitter (SIP-100, SIP-5000)
Warranty	1 Year (SIP-100, SIP-5000)

