


FM4X1/70


Foreground Music Speaker, Black Tuned enclosure, 70V/8-0hm, Rotary Select

FM4X1/70/W

Foreground Music Speaker, White Tuned enclosure, 70V/8-0hm, Rotary Select

FOREGROUND MUSIC LOUDSPEAKER SYSTEM







GENERAL DESCRIPTION

The QUAM FM4X1/70 is a complete 2-way loudspeaker with a 4" O.D. woofer and 3/4" dome tweeter, 20W-70.7V, low loss, extended frequency response rotary select transformer with 8-Ohm position, and multiple position "U" bracket.

SYSTEM COMPONENTS

Loudspeaker	8C5PAX
Transformer	70V or 8-Ohm, 5-tap Rotary Select (20W, 10W, 5W, 2.5W, 1.25W)

FINISH OPTIONS

FM4X1/70	Black
FM4X1/70/ W	White

AUDIO SPECIFICATIONS

Average Sensitivity	89 dB-SPL, 1W/1M
Loudspeaker Power Rating	20W RMS, EIA 426A Standard
8-Ohm Tap Output	89 dB-SPL, 1W/1M
Calculated Maximum System Output	102 dB-SPL, 20W/1M, 70.7V mode
Frequency Response	80 Hz-20 kHz EIA 426A Standard
Nominal Coverage Angle	90° included angle -6 dB/ 2 kHz half space
Audio Connection	Binding Screw

INTENDED USE

Protected outdoor or indoor environment, surface mount, horizontal or vertical installation Program Material: Signal tones, voice and music

Recommended construction sequences, installation instructions and A&E Specifications, are available in various formats in the QUAM Architects' and Engineers' Resources section on the web at: www.QuamSpeakers.com

QUAM-NICHOLS COMPANY

234 East Marquette Road, Chicago IL 60637 Phone: (800) NEED NOW Fax: (888) NEED NOW (800) 633-3669 (888) 633-3669

E-Mail: NeedNow@QNC.com www.QuamSpeakers.com

