LOUDSPEAKER ASSEMBLIES



FM4X1/70/W

FOREGROUND MUSIC

2-Way - 4" O.D. LF Speaker & 3/4" HF, 70V Rotary Select Transformer with 8Ω Tap, White Finish

GENERAL DESCRIPTION

The FM4X1/70/W is complete 2-way loudspeaker with a 4" O.D. Woofer, 3/4" dome tweeter, 20W-70V low loss, extended frequency response rotary select transformer with an 8 Ohm position in a white finish. Multiple position "U" braket included.

INTENDED USE - Indoor Environment

Program Material | Signal tones, voice, and music **Installation** Horizontal or Vertical Surface Mount

AUDIO SPECIFICATIONS

Average Sensitivity **Loudspeaker Power Rating** 8 Ohm Tap Output **Calculated Output** Frequency Response Nominal Coverage Angle

89 dB SPL, 1W/1M 20W RMS, EIA 426A Standard 89 dB SPL, 1W/1M 102 dB SPL, 5W/ 1M 80Hz - 20kHz EIA 426A Standard

90° Included Angle, -6 dB / 2 kHz, Half space


Audio Connection | Binding Screw


SYSTEM COMPONENTS

Loudspeaker Tweeter Transformer 4" O.D. Woofer 3/4" Dome Integral to Unit

20W-70V or 8 Ohm, 5 tap (20W, 10W, 5W, 2.5W, 1.25W)







Recommended construction sequences, installation instructions, and A&E Specifications are available in various formats in the QUAM Architects' and Engineers' Resources section on the web at: www.QuamSpeakers.com



