

# 1161A Series Category 3



## SPECIFICATIONS

Conductor	Tinned copper
Insulation	Polyolefin
Core Wrap	Non-hygroscopic, dielectric tape (16+ pair counts only)
Shield	Aluminum foil
Jacket	Gray PVC printed at 2 foot intervals including product identification, pair count, UL information and sequential lengths in feet and meters
Performance Compliance	Telcordia GR-137-CORE, Issue 2, May 2013 Telcordia GR-499-CORE (Pulse shape compliance at 565 feet) ASTM B33 - Tinned Copper UL 444 CSA C22.2 No. 214-08 UL 1666 ANSI/TIA-568-C.2 RoHS-compliant
NRTL Programs	UL, c(UL) Listed CMR

## PRODUCT DESCRIPTION

The 1161A Series Central Office (CO) Cables are designed for use between switching and transmission equipment, spanning distances up to 565 feet. With short twist lays, 1161A series offers superior crosstalk performance over standard telephone cable. It is manufactured with a foil shield for Electromagnetic Interference (EMI) reduction. The 1161A series meets or exceeds all applicable requirements of Telcordia GR-137 specifications.

## APPLICATIONS

- T1/DS1
- T1C/DS1C
- DS2

## FEATURES

- 24 AWG tinned copper conductors
- Solid color Polyolefin insulation
- 100 Ohm nominal Impedance
- Short pair lays/tight twists
- Aluminum foil shield
- Tinned copper drain wire
- CMR listed
- 75°C rating
- Rip cord

## BENEFITS

- Small diameter and light weight results in smaller bundles of cables and improved flexibility (compared with 600 Series)
- Tinned copper conductors minimize change in wire-wrap joint resistance
- Greater crush resistance and improved transmission characteristics
- Impedance mismatch with OSP cable is minimized
- Improved crosstalk performance and pair identification
- EMI isolation
- Easier termination and superior grounding
- Suitable for horizontal and riser installations
- Wider operating temperature range
- Added ease of jacket removal

## PART NUMBERS AND PHYSICAL CHARACTERISTICS

Part Number	Pair Count	AWG (mm)	Nominal Diameter in (mm)	Approx. Weight lbs/kft (kg/km)	Standard Length ft (m)	Package
55-299-21	4	24 (0.5)	0.26 (6.6)	27 (40)	10,000 (3,048)	Reel
55-399-21	6	24 (0.5)	0.27 (6.9)	35 (52)	10,000 (3,048)	Reel
55-F99-21	8	24 (0.5)	0.35 (8.9)	45 (67)	10,000 (3,048)	Reel
55-499-21	12	24 (0.5)	0.35 (8.9)	58 (86)	7,000 (2,133)	Reel
55-L99-21	14	24 (0.5)	0.38 (9.7)	70 (104)	7,000 (2,133)	Reel
55-599-21*	16	24 (0.5)	0.41 (10)	77 (115)	7,000 (2,133)	Reel
55-699-21*	20	24 (0.5)	0.44 (11)	93 (139)	20,000 (6,096)	Reel
55-799-21*	25	24 (0.5)	0.48 (12)	112 (167)	5,000 (1,524)	Reel
55-899-21*	28	24 (0.5)	0.51 (13)	123 (183)	5,000 (1,524)	Reel
55-999-21*	30	24 (0.5)	0.53 (14)	135 (201)	5,000 (1,524)	Reel
55-A99-21*	32	24 (0.5)	0.55 (14)	143 (213)	4,000 (1,219)	Reel
55-B99-21*	50	24 (0.5)	0.66 (17)	210 (313)	3,000 (914)	Reel
55-E99-21*	100	24 (0.5)	0.89 (23)	389 (579)	1,000 (305)	Reel

\*Mylar around core

## ELECTRICAL SPECIFICATIONS

Frequency MHz	PSNEXT Mean		PSNEXT Worst Pair	
	Minimum dB	Typical dB	Minimum dB	Typical dB
0.15	58	66	53	60
0.772	47	53	42	48
1.6	43	47	38	43
3.15	38	42	33	37
6.3	34	38	29	32

Attenuation @ 68°F (20°C)				Maximum Individual Conductor DC Resistance @ 68°F (20°C) Ohms/kft (Ohms/km)	Nominal Mutual Capacitance pF/ft (pF/m)	Characteristic Impedance @ 0.772 MHz Ohms
Bit Rate Mb/s	Frequency MHz	Maximum Average* dB/kft (dB/100 m)	Typical dB/kft (dB/100 m)			
1.544	0.772	6.3 (2.1)	5.4 (1.8)	28.6 (93.8)	16 (52)	102 ± 15.3

\*For cables with 12-pair or less, the maximum average attenuation may be increased by 10% over the values shown.