

INDOOR EMERGENCY PHONES

ETP-100M – Surface Mounting Emergency Phone

Description

The **ETP-100M** is an indoor hands-free Emergency Phone for use in locations such as: elevators, areas of rescue, stairwells, indoor controlled-access areas, senior citizen housing and correctional facilities.

Features

- Vandal resistant stainless steel faceplate and metal button
- Uses regular phone lines or PBX
- Phone line powered: no power supply or battery back-up needed
- Push button once to call, then speak hands-free
- LED indicator for hearing impaired
- Built-in auto-dialer can dial two numbers: if first number doesn't answer or is busy, dials second number.
- Auto-answer allows security to monitor and initiate calls with Emergency Phone
- Options available that offer the ability to automatically identify attendant of location of calling phone by recorded message and digital display



Construction: 22 gauge (0.64mm) #4 brushed stainless steel face plate

Dimensions: 4.81(122) W x 8.81(224) H x 2.5(64) D in(mm)

Weight: 4 lbs. (1.8kg)
Mounting: Surface mounts

Communication: 2-way hands-free communication

Digit Capacity: Up to 18 digits, including pauses, for each of two phone numbers

Dialing Speed: Approximately 10 tones per second

Power Source: Phone line powered (requires 20mA at 24 v off-hook)

Connection: Parallel tip and ring connected to RJ11 connector for quick installation

Circuit Protection: Varistor lightening suppressed and full wave polarity guarded

Programming: Non-volatile EEPROM programming can be done from any telephone.

No battery back-up is needed

"On Time": Programmable from 1-4270 minutes in 1 minute increments.

Wiring Requirements: 1 twisted-shielded pair

Options & Accessories

ADA Signage: Self-adhesive raised letter and Braille signage is available as model **ETP-MP**

Voice Location Identifier: Model **ETP-100MV** includes the capability to record a message identifying the location of the call. Message is recorded and duration set during programming.

ocation of the call. Message is recorded and duration set during programming.

Auxiliary Input/Outputs: Add "AUX" to model number. Input allows unit to be activated by any device that

creates a contact closure. Two outputs can activate a strobe or light as well as

remotely control a door, CCTV or other device.

8-Line Consolidator: Model **EC-8** allows connection of up to 8 phones on one phone line while retaining

ability to call each phone individually. Can also create a closed system without need

for any phone lines.

Scream Detector: Scream Alert™, model **SA-1**, automatically activates phone upon hearing a scream

(requires AUX option)

Monitoring/Diagnostic Talk-A-Lert®, model **ETP-TAL**, automatically polls each Emergency Phone, reports

Software Package: incoming calls and keeps permanent records of all events

Copyright 2009 Talk-A-Phone Co. All rights reserved.

YOUMAN SPEAK WHEN LIGHT IS ON

FOR HELP
PUSH ONCE
ALMS RECENTS NEW COMING

Rev. 7/20/09

ETP-100M - Surface Mounting Indoor Emergency Phone

Dimensions

