


**LCD-642 (Monitor with 2 video inputs)**



**LCD-640 (Monitor with audio)**



**LCD-642D Dual Rack Mount Unit**



**LM-642 Shown with Flush Mount Kit**



### MODEL NUMBERS

- LCD-642 Monitor with 2 Video Inputs
- LCD-642D Dual Monitors in Rack Mount Kit
- LCD-640 Monitor with Audio

### DESCRIPTION

- Slim space saving design
- For color and B&W applications
- Low power consumption
- Case made of durable ABS plastic
- Compact and light weight for easy installation or mobile use
- Active matrix technology allows wide viewing angle
- Active matrix technology eliminates distortion
- A/C adaptor Part No. AC-2000 included
- For LCD-642 mirror image capable (order optional Part No. LCD-642RCBL)
- LCD-640 KIT: 6" LCD Field Kit with rechargeable battery pack and tote bag
- LCD 642D: 6" dual rack mount kit (Two LCD-642 in standard 19" rack mount kit)

### OPTIONAL ACCESSORIES

- BP-563 Rechargeable 2200MAH battery pack. Provides approximately 5 hrs.of operation
- DC-12 Car Cord
- DC-12D Dual Car Cord
- HS-1 Hot Shoe mount
- LCD-642 RCBL Cable to affect mirror image for LCD-642
- LM-642 Flush mount kit, black metal 9.1"(W) x 8.3"(H) x 0.8"(D) Installer's Cut-Out: 7.1" (W) x 5.4" (H)
- MB-1 Desk Stand (shown above)
- MB-72M Mounting Brackett
- RM-642 Dual rack mount panel for 642, black metal 19"(W) x 7"(H) x1.5"(D) (occupies 4 RU) Included with 642D rack mount kit order
- TB-640 Custom Totebag with sunshield for 640
- WM-1 Wall mount bracket

### SPECIFICATIONS (LCD-640)

Brightness Rating	LCD-642: 250 cd/m <sup>2</sup> (Nit) LCD-640: 300 cd/m <sup>2</sup> (Nit)
Back Light	CCFT
Dot Format	960(H) x 234(V) dots
Dot Pitch	0.416mm(H) x 0.136mm(V)
Contrast Ratio	150 : 1
Display	6.4" TFT LCD active matrix
Number of Pixels	224,640 dots
Pixel Configuration	Stripe
Input Signal	NTSC / PAL (auto switching)
Input Signal Level	1.0 V P-P (positive) 75 Ohm
LCD-640: Audio IN	100 ~ 300mv (RMS)
LCD-640: Audio output	0.4W
LCD-640: Speakers	1.5"
Viewing angle (L/R/T/B)	45/45/10/30 degrees
Dimensions (WHD)	LCD-642: 180 x 135 x 35mm / 7.1" x 5.3" x 1.4" LCD-642D: 19" x 7" x 1.5 (Occupies 4 RU) LCD-640: 175 x 140 x 35mm / 6.8" x 5.5" x 1.4"
Visible screen size (WH)	130 x 98mm / 5.2" x 3.9"
Operating temperature	50~104°F or 10~40°C
Monitor Mounting	Mounting pad with ¼-20 threaded socket
Power Requirement / Consumption	12~24 VDC(ripple 0.5V p-p),1000mA,+ pin 8 W (max)
Connections	<b>LCD-642</b> DIN cable with 2 RCA composite video IN jacks, and 2.1mm DC IN jack (for power) <b>LCD-640</b> DIN cable with 1 BNC composite video IN jack, 1 RCA audio IN jack, and 2.1mm DC IN jack (for power)
Weight	<b>LCD-642 Net</b> 500g/17.5oz <b>Gross</b> 1.4 kg / 3.1 lbs <b>LCD-642D Net</b> 4.7 kg / 10.4 lbs <b>Gross</b> 5.4 kg / 12 lbs <b>LCD-640 Net</b> 0.6 kg / 1.2 lbs <b>Gross</b> 1.2kg / 2.6 lbs