

LED-1708HD

This LED-backlit monitor features the latest technology with enhanced picture clarity and sharpness for both analog and digital video signals.

Benefits

- Analog video is very clear with no detail loss
- Displays 1080i/p digital video
- 3D Comb Filter for better picture quality
- High contrast ratio for better picture definition
- Durable metal case

Related Products

- LED-1708HDR: 17" rack-mount LCD Monitor
- LED-1708HDL: 17" flush-mount LCD Monitor
- LED-1908HD: 19" standalone / wall-mount LCD Monitor
- LED-1908HDL: 19" flush-mount LCD Monitor
- LED-1908HDR: 19" rack-mount LCD Monitor
- LED-1908HDVB: 19" standalone / wall-mount LCD High Brightness Monitor

Specifications	
Mount	VESA 100mm x 100mm; Removable Deskstand
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Durable Metal
Native Aspect Ratio	5:4
Visible Screen Size (WH)	13.4" x 10.7" / 340 x 272mm
Resolution	1280(H) x 1024(V)
Brightness Rating	300 cd/m ²
Contrast Ratio	10,000:1
Back Light	LED (30K)
PC Compatibility	Yes
Dot Pitch	0.264(H) x 0.264(V)mm
Color Depth	16.7M
Number of Pixels	1,310,720
Response Time	5ms (Rising/Falling)
Audio Power / Speakers	2 Speakers x 1.5 Watts
Viewing Angle (L/R/T/B)	85/85/80/80 degrees
3D Comb Filter	Yes
Dimensions w/ Deskstand	14.9" x 13.1" x 2.9" / 378 x 331.5 x 72mm
Dimensions	14.9" x 13.1" x 2.9" / 378 x 331.5 x 72mm
Operating Temp	32 ~ 104°F / 0 ~ 40°C
Humidity	10% ~ 90%
Power Requirements	DC 12V (AC100~240)[50/60]
Composite	x2 BNC Inputs / Outputs
PC	x1 VGA 15-pin D-sub Input
HDMI	x1 Input
Audio	x1 L/R RCA Input; x1 3.5 PC stereo Input
Power	x1 2.1mm DC Input
Weight	Net: 9.95 lbs / 4.5 kg; Gross: 15.5 lbs / 7 kg
GSA	Yes

Specifications subject to change.