

LED-1908HDL

This LED-backlit flush monitor features the latest technology with enhanced picture clarity and sharpness for both analog and digital video signals.

Analog video is very clear with no detail loss
Displays 1080i/p digital video
3D Comb Filter for better picture quality
High contrast ratio for better picture definition
Durable metal case

LED-1708HD: 17" standalone / wall-mount LCD Monitor
LED-1708HDL: 17" flush-mount LCD Monitor
LED-1708HDR: 17" rack-mount LCD Monitor
LED-1908HD: 19" standalone / wall-mount LCD Monitor
LED-1908HDR: 19" rack-mount LCD Monitor
LED-1908HDVB: 19" standalone / wall-mount LCD High Brighness Monitor

Mount	VESA 100 x 100mm; Removable Deskstand
	Yes
	Yes
	Durable Metal
	Yes
	Yes
	16:9
	16.1" x 9.1" / 409.8 x 230.4mm
	1366(H) x 768(V)
	220 cd/m ²
	3000:1
	LED (30K)
	0.30(H) x 0.30(V)mm
	16.7M
	1,049,088
Response Time	9ms (Rising/Falling)
	8 Ohm, 2 Speakers x 2 Watts
	88/88/88/88 degrees
	Yes
	17.5" x 11.7" x 5.5" / 443 x 298 x 140mm
Dimensions	17.5" x 10.4" x 2.1" / 443 x 264 x 52mm
	41 ~ 95°F / 5 ~ 35°C
	20% to 80%
	110 VAC, 60 Hz
	30 Watts (Max)
Component ()	x1 RCA Input
Composite	x1 Input; Shared with Component
	x1 15-pin D-sub input
HDMI	x1 Input
	x1 3.5mm Input
USB	x1 Input (for updates only)
Audio	x1 S/PDIF audio Output; x1 3.5mm ear-phone Output
	x1 AC Input
	Net: 10.1 lbs / 4.6 kg; Gross: 13.7 lbs / 6.2 kg

Specifications subject to change.