

## DVI over Cat5/Cat6 Active Extender Kit, Wallplate Transmitter and Receiver, 1920x1080 at 60Hz

MODEL NUMBER: **B140-1A1-WP**



### Description

Tripp Lite's B140-1A1-WP DVI over Cat5 Active Extender Kit is perfect for those who need a wallplate solution that extends a DVI-D Single-Link signal up to 200 ft. from the source. When using 24Awg, solid wire Cat5e/6 cabling (Tripp Lite [N202-Series patch Cables](#)), the B140-1A1-WP can extend a 1024 x 768 (60Hz) signal up to 200 ft., or a 1920 x 1200 (60Hz) signal up to 150 ft. Installation is quick and easy: Simply plug a pre-terminated RJ45 patch cable between the two wallplates and connect the wallplates to the source and monitor using standard DVI-D Single-Link cables (Tripp Lite [P561-Series](#)). The signal will be sent with perfect video quality with equalization control at the receiver end, which allows adjustment for the sharpest image. Wallplates mount in standard in-wall electrical boxes or surface mount boxes. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

### Features

- 2 piece kit includes both local transmitter and remote receiver wallplates
- Extend a DVI-D Single-Link signal up to 200 ft. at 1024 x 768 (60Hz), or up to 150 ft. at 1920 x 1200 (60Hz), when using 24Awg, solid wire Cat56 cabling. (Tripp Lite [N202 Series Patch Cables](#))
- Built in equalization control for the sharp display quality
- Easy RJ45 patch cable connections
- No software or drivers required
- HDCP and DDC compatible
- Compatible with all operating systems
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

## Specifications

### General Info

### Highlights

- DVI Single-Link video over Cat5e or Cat6 cabling
- Easy RJ45 connection on back of wallplates
- Equalization control for the sharp display quality
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### Applications

Long distance connection (up to 200 ft.) of a DVI source to a TV, monitor or other video display for presentations, digital signage and POP displays.

### System Requirements

- DVI Video card and DVI Monitor

### Package Includes

- B140-1A1-WP Local Wallplate
- B140-1A1-WP Remote Wallplate
- 2 x AC Power adapters
- Wallplate screws
- Screwdriver for Equalization adjustment



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

RoHS	Y
<b>OVERVIEW</b>	
Chromebook Compatible	No
Display Style	Extender
Model Type	DVI
Cable Types	CAT6
<b>USER INTERFACE, ALERTS &amp; CONTROLS</b>	
LED Indicators	The LED on the local unit illuminates to indicate it is connected to, and receiving power from, the source. The LED on the remote unit illuminates to indicate it is connected to, and receiving power from, the monitor.
<b>PHYSICAL</b>	
Color	White
<b>CONNECTIONS</b>	
Connector A	RJ45 (FEMALE) (X2)
Connector B	DVI-I (FEMALE) (X2)
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.