



VZ-PVM-I2W3 ADVANTAGES

- 23" iP Public View Monitor
- **Onvif Compliant (Fully Compatible with VMS) - Profile S**
- "A" Commercial Grade LED
- Built in 2.1 Mega Pixel Camera
- Camera Motion Sensor
- Timed Source Switching
- Auto Power / Source Recovery
- 600 TV Line - Analog Video Resolution
- PIP / PBP / VOV
- BNC(NTSC/PAL), VGA, 2 HDMI, DVI, PC Stereo
- 3D Comb-filter, De-interlace
- Support dual voltage solution (110V AC and 24V DC)
- 3-Year Warranty



MODEL #	VZ-PVM-I2W3
DISPLAY	
Screen Size	23"
Max. Resolution	1920 x 1080 @60Hz
Pixel Pitch	0.2655mm x 0.2655mm
Brightness	250cd/m²(Typical)
Contrast Ratio	1000:1
Aspect Ratio	16 : 9
Viewing Angle (H/V)	160° / 160°
Display Color	16.7 Million
Response Time	< 5 ms
Video System	NTSC / PAL
Frequency (H) / Frequency (V)	31 ~ 80Khz / 56 ~ 75Hz

INTERFACE	
AV (Composite) In / Out	1 / 1
Camera Out	1
DVI - In / HDMI In / VGA In (15Pin D-Sub)	1 / 2 / 1
PC Stereo In / Out	1 / 1

SPECIAL FEATURES	
Multi Display Function	PIP / PBP / VOV
Filter Type	3D Comb-filter / De-Interlace
Analog Video Resolution (MAX)	600 TV Line
Multi-lingual Language	English, Spanish, French, German, Italian, Portuguese, Dutch

DIMENSIONS & WEIGHT	
Outline Dimension (W x H x D)	21.25" x 16.18" x 3.27"
	539.8mm x 411mm x 83mm
Net Weight / Gross Weight	21.67 lbs (9.83 kg) / 29.76 lbs (13.5 kg)

MOUNT	
VESA	100mm x 100 mm / M4 x 8 Screws 200mm x 200mm / M6 x 8 Screws

GENERAL	
Transmitter - IR Remote Control	YES
Power	Electrical Ratings Consumption
	AC 110~240V (50/60Hz) 50W
Warranty	Parts/ Labor MTBF (Approx.)
	3 Year / 3 Year 50,000 Hours
Operating Temperature	32 - 104°F / 0 - 40°C
Regulation	TUV-NRTL (=UL), FCC(A)
Compatible Mounts	Wall Ceiling
	VZ-WM50, VZ-AM02 VZ-CM06, VZ-CM18, VZ-CMK01, VZ-CMK03

CAMERA	
Camera Type	2.1 Mega Pixel IP Camera
Image Sensor	Panasonic 2.1 Mega Pixel C-MOS Sensor
Lens	DC Auto Iris 2.8~12mm Vari-focal Lens
Total / Effect Pixel	1920(H) x 1080p(V) 30fps
Video Compression	H.264, CBR, VBR support
Video Out	1ch CVBS (NTSC/PAL) / 1ch RJ-45 output
Motion Detection	Support
Ethernet Port	10 / 100 Base-T
Webclient Connection Protocol	TCP / IP
Support Protocol	IHTTP, TCP/UDP/IP, ARP, ICMP, RTP/RTSP, Multicast, Telnet, ftp, PPPoE, SMTP(e-mail), DHCP, NTP, uPNP, etc, ONVIF, PSIA support
Function	2D/3D NR, D-ZOOM, DPC, HLC/BLC, Defog D/N, DWDR, AGC, AWB, IR SMART
Dynamic IP	Dedicated dynamic IP service using www.ipcctvdns.com

MEDIA CARD - Optional Feature	
External Storage	Support SD/SDHC CARD, USB 2.0 HOST
Output	VIDEO - HDMI(1080p) / AUDIO - L/R, HDMI
VIDEO Format	RM, RMVB, AVI, DVIX, MKV, MOV, HDMOV, MP4, M4V, PMP, AVC, FLV, VOB, MPG, DAT, MPEG, TS, TP, M2TS, WMV, H.264, H.263, WMV9, VC-1, MPEG1/2/4
VIDEO Resolution	1080P @60Hz
AUDIO Format	MPEG1/2/4, MP3, WMA, OGG, AAC, FLAC, APE, AC-3, DTS, ATRA, WAV, PCM
Image Format	JPEG, TIF, PNG, BMP
VIDEO Play Control	AUTO, REPEAT, ZOOM, RESUME, TIME

Contact ViewZ

- Address : 177 W. Orangethorpe Ave., Placentia, CA 92870
- Phone : (714) 996-1177, Fax : (714) 996-1138
- Sales : sales@viewzusa.com
- Specification subject to change without notice.

