

**STANLEY**  
®

Security Solutions

PADLOCKS



**3 SERIES**  
PADLOCKS



TABLE OF CONTENTS	Page	Page	
General Information.....	2	21BSH Shroud Option.....	6
Shackle Chart / Patented Keying .....	2	21JB Series Cable.....	7
11B/12B Series .....	3	Lockout/Tagout .....	8
21B/22B Series .....	4	Accessories / Options / Tools .....	9, 10
41B/42B Series .....	5	Repair and Parts Exploded Views.....	11

## GENERAL INFORMATION

The heart of every Best Access Systems padlock is a standard key removable core which is interchangeable throughout most of the entire line of BEST products. This standardization permits BEST locks of any type, size or style to be masterkeyed into one system which can expand to include future locking needs.

## B SERIES SHACKLE CHART

Shackle Material	Brass			Stainless Steel			Hardened Steel		
Series	11B	21B	41B	11B	21B	41B	11B	21B	41B
Shackle Diameter	1/4"	5/16"	3/8"	1/4"	5/16"	3/8"	1/4"	5/16"	3/8"
ASTM Grade	x	x	x	3	4	3	4	4	4
Cut Resistance	x	x	x	3	4	5	6	6	6
Corrosion	x	x	x	6	6	6	6	6	6
Tensil	x	x	x	4	4	4	4	4	4
Shock	x	x	x	6	4	3	4	4	4

## PATENTS

Products protected by one or more of the following patents:

3,603,123	4,075,878	3,882,699
3,850,014	3,652,114	3,728,879
3,605,458	4,244,093	4,386,510
4,424,693	4,444,034	4,655,063
D290,085	Other patents pending.	

## PATENTED KEYING

**BEST Peaks®**— For advanced solutions in key control and security, BEST offers Peaks®, the most adaptable and cost effective patented keying system on the market. The patented mechanism ensures that cylinders and cores will only operate with the Peaks® keys, which are only available through authorized BEST distributors.

For BEST products, Peaks® offers the security and convenience of a patented solution for interchangeable core. Peaks® is also available to adapt to a wide variety of locks from other manufacturers. All cylinders can be keyed into the same system, providing you the ability to operate all the locks at your facility using a single key, regardless of the lock manufacturer.



**BEST Peaks®  
Patented Keying**

**Specifications****Case**— Machined from solid extruded brass or aluminum.


Standard finish is 626 satin chromium plated.

**Width**—  $1\frac{5}{8}$ "**Length**—  $2\frac{1}{16}$ "**Thickness**—  $\frac{25}{32}$ "**Shackle**— The shackle locks at both heel and toe.


The length of shackle opening is measured from top of case to inside of shackle when padlock is locked.

**Material**— Brass or stainless steel**Diameter**—  $\frac{1}{4}$ "**Width of opening**—  $\frac{7}{8}$ "**ASTM F883**— Meets Grade 3 with stainless steel shackle.**ASTM F883**— Meets Grade 6 for option E. (Corrosion resistance).


11B Padlock



11B72 Actual Size



11B722 Actual Size



11B772 Actual Size

11B782 Actual Size

**11B/12B — HOW TO ORDER**

11B	7	2	T		Special	Options Stamp No.	
Shackle Diameter	Core Housing	Shackle Height	Function Code	Chain Option			
11B— brass $\frac{1}{4}$ " diameter 12B— aluminum $\frac{1}{4}$ dia.	7—7 pin housing accepts all Best cores	Steel shackle  <b>2</b> — $\frac{3}{4}$ " <b>22</b> — $1\frac{1}{2}$ " <b>72</b> —2" <b>82</b> —4"  <b>Brass shackle</b>  <b>0</b> — $\frac{3}{4}$ " <b>20</b> — $1\frac{1}{2}$ " <b>70</b> —2" <b>80</b> —4"	T—key retained  L—non-key retained	M—case drilled for clevis only  M1—bronze chain (11B only)  M5—galvanize steel chain with gray polycoating (page 9)	Blank— Best logo  PS1010— safety first (11B only)  (Specify padlock stamp number or describe stamp.)  M5—galvanize steel chain with gray polycoating (page 9)	Blank— Best logo  PS1010— safety first (11B only)  (Specify padlock stamp number or describe stamp.)  M5—galvanize steel chain with gray polycoating (page 9)	F3—frangible shackle (11B720 only)  606—satin brass (11B only)  ZZ—double lockout (11B only)  Red—anodized finish (12B only)  Black—anodized finish (12B only) (pages 9-10)

O

C

K

S

**21B/22B SERIES****Specifications**

**Case**— Machined from solid extruded brass or aluminum.

Standard finish is 626 satin chromium plated.

**Width**— 1  $\frac{25}{32}$ "

**Length**— 2  $\frac{1}{16}$ "

**Thickness**—  $\frac{13}{16}$ "

**Shackle**— The shackle locks at both heel and toe. The length of shackle opening is measured from top of case to inside of shackle when padlock is locked.

**Material**— Bronze or stainless steel

**Diameter**—  $\frac{5}{16}$ "

**Width of opening**—  $\frac{7}{8}$ "


**ASTM F883**— Meets Grade 4 with stainless steel shackle.

**ASTM F883**— Meets Grade 6 for shackle cutting force with XSPL shackle option.


**ASTM F883**— Meets Grade 6 for option E. (Corrosion resistance).




**21B Padlock**



**21B72 Actual Size**



**21B722 Actual Size**



**21B772 Actual Size**



**21B782 Actual Size**

**21B/22B — HOW TO ORDER**

21B	7	2	T			
Shackle Diameter	Core Housing	Shackle Code	Function	Chain Option	Special Stamp No.	Options
21B— brass $\frac{5}{16}$ " dia.	7— 7 pin housing accepts all Best cores	<b>Steel shackle</b> 2— $\frac{3}{4}$ " 21— 1" w/shroud 22— 1 $\frac{1}{2}$ " 72— 2" 82— 4"  <b>Brass shackle</b> 0— $\frac{3}{4}$ " 20— 1 $\frac{1}{2}$ " 70— 2" 80— 4"	T— key retained L— non-key retained	M— case drilled for clevis only  M1—bronze chain (21B only)  M5—galvanize steel chain with grey polycoating	Blank—Best logo PS1010—safety first (21B only) <b>(Specify padlock stamp number or describe stamp. (21B only) Price for special stamps on request.)</b>	606—satin brass (21B only) SH—shrouded with cut resistant shackle (21B only) WC—weather cover XSPL—cut resistant shackle Red— anodized finish (22B only) Black— anodized finish (22B only)
22B— aluminum $\frac{5}{16}$ " dia.				(page 9)	(page 9)	(pages 9-10)

## Specifications

**Case**— Machined from solid extruded brass or aluminum.

Standard finish is 626 satin chromium plated.

**Width**— 1  $\frac{15}{16}$ "

**Length**— 2  $\frac{1}{16}$ "

**Thickness**—  $\frac{7}{8}$ "

**Shackle**— The shackle locks at both heel and toe.

The length of shackle opening is measured from top of case to inside of shackle when padlock is locked.

**Material**— Bronze or stainless steel

**Diameter**—  $\frac{3}{8}$ "

**Width of opening**—  $\frac{7}{8}$ "

**ASTM F883**— Meets Grade 3 with stainless steel shackle, grade 4 with XSPL shackle.


**ASTM F883**— Meets Grade 6 for option E. (Corrosion resistance).

**ASTM F883**— Meets Grade 6 for shackle cutting force


with XSPL shackle option




41B Padlock




41B72 Actual Size



41B722 Actual Size



41B772 Actual Size



41B782 Actual Size

## 41B/42B — HOW TO ORDER

41B	7	2	T		Special Stamp No.	Options
Shackle Diameter	Core Housing	Shackle Height	Function	Chain Option		
41B— brass $\frac{3}{8}$ " diameter	7— 7 pin housing all Best cores	<b>Steel shackle</b> 2— $\frac{3}{4}$ " 22— 1 $\frac{1}{2}$ " 72— 2" 82— 4"	T— key retained L— non-key retained	M— case drilled for chain M1— bronze chain (41B only) M5— galvanize steel chain with gray polycoating	Blank— Best logo (Specify padlock stamp number or describe stamp. (41B only.) Price for special stamps on request.)	606— satin brass (41B only) S— car seal slot (41B only) WC— weather cover XSPL— cut resistant shackle Red— anodized finish (42B only) Black— anodized finish (42B only)
42B— aluminum $\frac{3}{8}$ " diameter		<b>Brass shackle</b> 0— $\frac{3}{4}$ " 20— 1 $\frac{1}{2}$ " 70— 2" 80— 4"			(page 9)	(pages 9-10)

O

C

K

S



**21B Padlock with Stainless Steel Shroud on hinge hasp (not supplied)**



**21B with Stainless Steel Shroud**

## Features & Benefits

- Cast stainless steel shroud with black powder-coated finish
- Through hardened shackle for cut resistance
- Utilized same internal components and body as standard 21B padlock
- Accepts all Best cores, with Standard, Premium, Peaks™ keying system
- Meets ASTM F883 Grade 4; meets Grade 6 for cut resistance
- Available in either key retained or non-key retained

## 21B SHROUD – HOW TO ORDER

21B	7	21	L			SH
Shackle Diameter	Core	Shackle Housing	Function Code	Chain Option	Special Stamp No.	Options
21B- 5/16" dia.	7- 7-pin housing accepts all BEST cores	21- 1" shackle opening	T- key retained L- non-key retained	N/A for shroud option	N/A for shroud option	SH- shroud with cut resistant shackle (21B only)

## Specifications

**Case**— Machined from extruded brass. Standard finish 626 satin chromium plated.

**Width**—  $1\frac{25}{32}$ "

**Length**—  $2\frac{1}{16}$ "


**Thickness**—  $\frac{27}{32}$ "

**Shackle Cable**: Diameter  $\frac{1}{8}$ " stainless steel. Length variable.

18" standard unless specified other length.

**Cable jacket**: A tough plastic coating protects vulnerable surfaces.

Measure cable length from top of case to top of case.



21JB7 - 18

## 21JB – HOW TO ORDER

Series Housing	Core Length	Cable	Options
21JB—cable padlock	7—7 pin housing accepts all Best cores	18—18" 24—24" 36—36" 42—42" 48—48" 54—54"	606—clear coated satin brass

## LOCKOUT / TAGOUT

OSHA requires that a Lockout/Tagout system be placed upon energy control devices to ensure that machines and equipment are isolated from all energy sources before employees perform service or maintenance activities. This is particularly necessary where the unexpected energization, start-up, or release of stored energy could cause injury or equipment damage. Stanley Security Solutions' Lockout/Tagout system includes six durable PVC vinyl coated BEST padlocks with Lockout/Tagout devices (11B/12B, 21B/22B, 41B/42B).


The OSHA vinyl coated padlocks will not chip or corrode. They also resist acids, oils or abrasions. Available is an OSHA accepted 6-padlock red polyresin coated aluminum lockout (BD655), and easy-to-read energy source identification tags. In addition to names of the workers, our tags can provide pertinent information, i.e. where the worker can be located. Details of OSHA Lockout/Tagout standard can be found in the code of Federal Regulations for labor at Title 29 part 1910.147, the control of hazardous energy Lockout/Tagout.




**Lockout/Tagout Padlocks**



**Lockouts**  
**BD655**



**Front**  
**Identification Tag**  
**BD657** (includes one tie per tag)  
**Tagout Tag**  
**BD658** (includes one tie per tag)




**Back**  
**Identification Tag**

## LOCKOUT/TAGOOUT PADLOCKS – HOW TO ORDER

11B Padlock Series	7	2	T Function Option	Chain	Special Stamp No.	O/ORA Options
11B/12B- $\frac{1}{4}$ "	7- 7 pin					Vinyl Cases
21B/22B- $\frac{5}{16}$ "	housing accepts all Best cores					O/RED- Red
41B/42B- $\frac{3}{8}$ "				For specific order procedures and complete specifications, see pages 3 through 7		O/YEL- Yellow O/BLU- Blue O/BLA- Black O/ORA- Orange O/GRE- Green

## Special Stamped Padlocks

Upon special request, and at no charge other than the initial cost of the die, BEST padlocks may be die-stamped with the customer's identification as specified. If stamp has been previously ordered, specify stamp number. (Brass padlocks only.)



Samples of Padlock Stamping

## F3– Option Frangible Shackle

Available in 11B series only. The frangible shackle pad lock is designed for fire and safety equipment, cabinets, etc. where casual entry needs to be prevented. During emergency, the shackle may be snapped by a hard blow or strong, steady pressure permitting entry without use of a key. (Check lock regulations). A brass  $1\frac{1}{2}$ " – number 20 size shackle is made frangible through use of special break point. Broken shackles are easily replaced in the field and may be ordered separately. A complete frangible shackle kit (including three frangible shackles, three shackle springs and one padlock disassembly tool) may be ordered with each padlock order.

To order kit specify: 11BFK



## M-Option Chains

Chains may be supplied with padlock. When ordering clevis and chains, add M1 or M5 to padlock nomenclature. Standard chain length is 9", special length chains available upon request.



M1 – 9"  
Bronze Chain

M5 – 9"  
Galvanized Steel Chain with  
Gray Plastic Polycoat Cover

## ACCESSORIES AND OPTIONS

### S- Option Car Seal Feature

Available in all 41B padlocks. Case is slotted below the core to accommodate most popular car seal bands. When in place, car seal band insures tampered with. Seals are available direct from car seal manufacturers. A special long blade key is required for 7-pin systems. When ordering simply add "S" to the option column of the 41B nomenclature.



41B car seal feature

### SH- Option Shrouded Padlock

Available in 21B padlocks. Cast stainless steel shroud with black powder-coated finish. Features hardened shackle for cut resistance. When ordering add "SH" to option column of the pad lock nomenclature.



21B shroud option

### WC- Option Weather Covers

Available in 21B/22B and 41B42B padlocks. The padlock weather covers are molded durable PVC that won't chip or corrode and resists acids, oils and abrasion. When ordering add "WC" to option column of the padlock nomenclature.



21B & 41B weather option

### ZZ- Option Double Lockout/Safety First

Available in 11B only, the double lockout safety padlock provides additional safety for maintenance crews making repairs in widely separated areas. The shackles of 11B padlocks are passed through holes in the extended skirt at the base of this lock. As long as either 11B padlock remains in place, the lock-out safety padlock cannot be unlocked. Elliptical solid brass case is  $1\frac{1}{2}$ " wide and is stamped with words "**Safety First**" on one side. Holes at base of case will accommodate 11B shackles only. Minimum shackle opening should be  $1\frac{1}{4}$ ". A long blade key is required for 7-pin systems. Dust cover cannot be used with double lockout.




11B double lockout option


## PADLOCK REPAIR AND PARTS

## 11B/12B – 21B/22B – 41B/42B Series

With the simplest of tools, proper replacement parts and minimal training, all BEST padlocks can be used for the duration of any installation. Listed below are the parts and tools required for the various series of padlocks. Contact your local Stanley Security Solutions office for special instruction and information about factory seminars for padlock repair. BEST padlocks can be repaired and worn parts replaced, virtually eliminating padlock replacement costs.



O C K S



For more information on Stanley Security Solutions' products, services, and office locations visit our web site at [www.stanleysecuritysolutions.com](http://www.stanleysecuritysolutions.com)

Product information contained in this catalog has been compiled and presented with as much care and completeness as is reasonably possible. Errors or mistakes may be present, and in many cases, reliance has been placed on information supplied by other manufacturers which may be in error or which may be subject to changes or modifications by the manufacturer without notice and without obligation. Therefore, no guarantee can be made or should be assumed or implied with regards to product information contained in this catalog.



Security Solutions

Stanley Security Solutions, Inc.  
6161 E. 75th Street Indianapolis, Indiana 46250  
[www.stanleysecuritysolutions.com](http://www.stanleysecuritysolutions.com)  
© 2007 Stanley Security Solutions, Inc. and Stanley Logistics

10M 707  
BAS028