

PIN TUMBLER DEADBOLT LOCKS & ACCESSORIES







Deadbolt Locks For Doors

Surface Mounted

- Requires 57/64" diameter hole for cylinder.
- Key required to engage lock and is removable in both locked and unlocked positions.
- Advantage PLUS feature makes key changes easier by allowing you to remove the cylinder while the lock remains in place with a 5/64" allen wrench-no mounting screws need to be removed.
- All are ANSI/BHMA certified Grade 2 A156.11.
- Supplied with two keys, strike and mounting screws.
- If trim ring is required, see NLC2017 Series on page D-28.
- Stock Keying is specified on table below:

KA - All Keyed Alike to key number specified, master key will not work on these locks

KD = All Keyed Different, various lock numbers, master key will not work on these locks

Packing: 10 each per box.

Sold in: Both broken and full box quantities.

Discount available for full box orders.

Keying	Cylinder Length	Bolt Travel	Satin Brass Item #	Satin Chrome Item #
KA 101	7/8"	3/4"	-	NLC8173KA101-26D
KA 103	7/8"	3/4"	-	NLC8173KA103-26D
KA 107	7/8"	3/4"	-	NLC8173KA107-26D
KA 915	7/8"	3/4"	NLC8173KA915-4	NLC8173KA915-26D
KD	7/8"	3/4"	-	NLC8173KD-26D
KA 915	1-1/8"	3/4"		NLC8174KA915-26D
KA 915	1-3/8"	3/4"	-	NLC8175KA915-26D



Extra Keys For Disc Tumbler Locks

Packing: As shown below.

Sold in: Both broken and full box quantities.

Discount available for full box orders.

