

# FRAMELESS SHOWER DOOR HARDWARE AND SUPPLIES

NEW PRODUCTS SUPPLEMENT

SD16SUP CATALOG

Crystal Glass & Mirror Corp.

An ISO9001:2008 Certified Company



**C.R. LAURENCE COMPANY**

Worldwide Manufacturer and Supplier

Glazing, Architectural, Railing, Screen, Construction, Industrial, and Automotive Supplies

[crlaurence.com](http://crlaurence.com)

[usalum.com](http://usalum.com)

[crl-arch.com](http://crl-arch.com)

# CRL SHOWER DOOR HINGES

Go to [crlaurence.com/shower-hinges](http://crlaurence.com/shower-hinges) for Available Finishes

## Adjustable Vienna Series Hinges

3/8" to 1/2"



### MODEL V1E344

Offset Wall Mount Plate  
Opens up to 90 Degrees  
Outward and Inward

#### SPECIFICATIONS:

**Glass Thickness:** 3/8" to 1/2" (10 to 12 mm) Tempered Safety Glass

**Special Feature:** Adjustable to Any Angle Up to 90 Degrees Without Having to Take the Door Down

**Construction:** Solid Brass

**Closing Type:** Self-Centering When Within 15 Degrees of Closed Position

**Cut-Out Required**

**Includes:** Gaskets, Phillips Screws, Allen Screws, and Glass Fabrication Dimensions

**NOTE:** Door glass width may require alteration from standard clearance deductions when adjusting angles. Call for details.

*MAXIMUM CAPACITIES	3/8" (10 MM) GLASS		1/2" (12 MM) GLASS	
	WEIGHT	DOOR WIDTH	WEIGHT	DOOR WIDTH
Using Two Hinges	100 lbs/45 kg	34"/864 mm	100 lbs/45 kg	32"/813 mm
Using Three Hinges	130 lbs/59 kg	34"/864 mm	130 lbs/59 kg	32"/813 mm

\* NOTE: Do not exceed maximum door weight or width when choosing proper quantity of hinges.

## Positive Close Vienna Series Hinges

3/8" to 1/2"



### MODEL V1E067

Wall Mount Full Back Plate  
Factory Set for Positive  
Closing to Zero Degrees



### MODEL V1E780

180° Glass-to-Glass  
Factory Set for Positive  
Closing to Zero Degrees

#### SPECIFICATIONS:

**Glass Thickness:** 3/8" to 1/2" (10 to 12 mm) Tempered Safety Glass

**Construction:** Solid Brass

**Hinge Swings:** 90 Degrees Inwards and Outwards

**Closing Type:** Positive Closing to Zero Degrees

**Cut-Out Required**

**Includes:** Gaskets, Phillips Screws, Allen Screws, and Glass Fabrication Dimensions

*MAXIMUM CAPACITIES	3/8" (10 MM) GLASS		1/2" (12 MM) GLASS	
	WEIGHT	DOOR WIDTH	WEIGHT	DOOR WIDTH
Using Two Hinges	110 lbs/50 kg	36"/914 mm	110 lbs/50 kg	36"/914 mm
Using Three Hinges	140 lbs/63 kg	36"/914 mm	140 lbs/63 kg	36"/914 mm

\* NOTE: Do not exceed maximum door weight or width when choosing proper quantity of hinges.



# CRL SHOWER DOOR HINGES

Go to [crlaurence.com/shower-hinges](http://crlaurence.com/shower-hinges) for Available Finishes

## Positive Close Cologne Series Hinges

3/8" to 1/2"



**MODEL C0L067**  
Wall Mount Full Back Plate  
Factory Set for Positive  
Closing to Zero Degrees



**MODEL C0L780**  
180° Glass-to-Glass  
Factory Set for Positive  
Closing to Zero Degrees

### SPECIFICATIONS:

**Glass Thickness:** 3/8" to 1/2" (10 to 12 mm) Tempered Safety Glass

**Construction:** Solid Brass

**Hinge Swings:** 90 Degrees Inwards and Outwards


**Closing Type:** Positive Closing to Zero Degrees

**Cut-Out Required**

**Includes:** Gaskets, Phillips Screws, Allen Screws, and Glass Fabrication Dimensions

*MAXIMUM CAPACITIES	3/8" (10 MM) GLASS		1/2" (12 MM) GLASS	
	WEIGHT	DOOR WIDTH	WEIGHT	DOOR WIDTH
Using Two Hinges	110 lbs/50 kg	36"/914 mm	110 lbs/50 kg	36"/914 mm
Using Three Hinges	140 lbs/63 kg	36"/914 mm	140 lbs/63 kg	36"/914 mm

\* NOTE: Do not exceed maximum door weight or width when choosing proper quantity of hinges.



Chattahoochee Glass and Shower Door

## Prima Series Bottom Mount Hinge With Rear Drip Plate

5/16" to 3/8"

- Attractive Drip Plate on Rear of Hinge Deflects Water Back Into the Shower
- Can Be Used in Conjunction With Other Prima Series Hinges Mounted at Top of Door (see [crlaurence.com/shower-hinges](http://crlaurence.com/shower-hinges))



**MODEL PPH08**



**MODEL PPHWP1**  
Replacement Rear  
Drip Plate Only

### SPECIFICATIONS:

**Glass Thickness:** 5/16" to 3/8" (8 to 10 mm) Tempered Safety Glass

**Construction:** Solid Brass

**Hinge Swings:** Full Rotation

**Closing Type:** Self-Centering When Within 15 Degrees of Closed Position

**Cut-Out Required**

**Includes:** Gaskets, Phillips Screws, Allen Screws, and Glass Fabrication Dimensions

*MAXIMUM CAPACITIES	5/16" (8 MM) GLASS		3/8" (10 MM) GLASS	
	WEIGHT	DOOR WIDTH	WEIGHT	DOOR WIDTH
Using Two Hinges	100 lbs/45 kg	31"/787 mm	100 lbs/45 kg	31"/787 mm

\* NOTE: Do not exceed maximum door weight or width when choosing proper quantity of hinges.

## Prima Series 135 Degree Glass-to-Glass Hinges With Attached U-Clamp

5/16" to 3/8"

- Alternative to Using Traditional Header Systems (See Design Criteria at [crlaurence.com](http://crlaurence.com))
- Typically Used With Model PPH01 Mounted at Bottom of Door
- Handed Left or Right



**MODEL PPH0735**  
(Left Hand Mount Viewed  
from Outside of Shower)

### SPECIFICATIONS:

**Glass Thickness:** 5/16" to 3/8" (8 to 10 mm) Tempered Safety Glass

**Construction:** Solid Brass

**Hinge Swings:** Full Rotation

**Closing Type:** Self-Centering When Within 15 Degrees of Closed Position

**Cut-Out Plus Hole Required**

**Includes:** Gaskets, Phillips Screws, Allen Screws, and Glass Fabrication Dimensions

*MAXIMUM CAPACITIES	5/16" (8 MM) GLASS		3/8" (10 MM) GLASS	
	WEIGHT	DOOR WIDTH	WEIGHT	DOOR WIDTH
Using Two Hinges	100 lbs/45 kg	31"/787 mm	100 lbs/45 kg	31"/787 mm

\* NOTE: Do not exceed maximum door weight or width when choosing proper quantity of hinges.

# CRL SHOWER DOOR HINGES

Go to [crlaurence.com/shower-hinges](http://crlaurence.com/shower-hinges) for Available Finishes

## Riviera Series Hinges

- Hinges Lift Door When Opening to Avoid Bottom Sweep Dragging
- Hinges are Handed Left or Right

5/16" to 3/8"



**MODEL R1V180**  
180° Glass-to-Glass  
Opens Up to 180 Degrees Outward



**MODEL R1V037**  
Wall Mount  
Opens Up to 90 Degrees Outward

### SPECIFICATIONS:

**Glass Thickness:** 5/16" to 3/8" (8 to 10 mm) Tempered Safety Glass

**Construction:** Solid Brass

**Hinge Swings:** Outward Only

**Closing Type:** Self Closes from Approximately 60 Degrees

**Countersunk Holes Required**

**Includes:** Gaskets, Phillips Screws, Allen Screws, and Glass Fabrication Dimensions

*MAXIMUM CAPACITIES	5/16" (8 MM) GLASS		3/8" (10 MM) GLASS	
	WEIGHT	DOOR WIDTH	WEIGHT	DOOR WIDTH
Using Two Hinges	80 lbs/36 kg	28"/711 mm	80 lbs/36 kg	28"/711 mm
Using Three Hinges	120 lbs/54 kg	34"/864 mm	120 lbs/54 kg	34"/864 mm

\* NOTE: Do not exceed maximum door weight or width when choosing proper quantity of hinges.



## Geneva Series T-Configuration Glass-to-Glass Hinge

- Ideal for "T" Configuration Double Door Enclosures

5/16" to 1/2"

**MORE FINISHES**  
[crlaurence.com](http://crlaurence.com)



**MODEL GENT90**  
Both Sides Open 90 Degrees  
Outward and Inward

### SPECIFICATIONS:

**Glass Thickness:** 5/16" to 1/2" (8 to 12 mm) Tempered Safety Glass

**Construction:** Solid Brass

**Hinge Swings:** 90 Degrees Inward and Outward

**Closing Type:** Self-Centering When Within 15 Degrees of Closed Position

**Cut-Out and Holes Required**

**Includes:** Gaskets, Phillips Screws, Allen Screws, and Glass Fabrication Dimensions

*MAXIMUM CAPACITIES	5/16" AND 3/8" (8 AND 10 MM) GLASS		1/2" (12 MM) GLASS	
	WEIGHT	DOOR WIDTH	WEIGHT	DOOR WIDTH
Using Two Hinges	80 lbs/36 kg	28"/711 mm	80 lbs/36 kg	28"/711 mm
Using Three Hinges	120 lbs/54 kg	32"/813 mm	120 lbs/54 kg	32"/813 mm


\* NOTE: Do not exceed maximum door weight or width when choosing proper quantity of hinges.

## Pinnacle Series Pony Wall Mount Hinge

5/16" to 1/2"



**MODEL P1N280**  
For Use In 180 Degree  
Applications



### SPECIFICATIONS:

**Glass Thickness:** 5/16" to 1/2" (8 to 12 mm) Tempered Safety Glass

**Construction:** Solid Brass

**Hinge Swings:** 90 Degrees Inward and Outward

**Cut-Out Required**

**Includes:** Gaskets, Phillips Screws, Allen Screws, and Glass Fabrication Dimensions

*MAXIMUM CAPACITIES	5/16" AND 3/8" (8 AND 10 MM) GLASS		1/2" (12 MM) GLASS	
	WEIGHT	DOOR WIDTH	WEIGHT	DOOR WIDTH
Using Two Hinges	80 lbs/36 kg	28"/711 mm	80 lbs/36 kg	28"/711 mm
Using Three Hinges	120 lbs/54 kg	32"/813 mm	120 lbs/54 kg	32"/813 mm

\* NOTE: Do not exceed maximum door weight or width when choosing proper quantity of hinges.

# CRL TOWEL BARS AND GRAB BARS



See Our Complete Line of Towel Bars, Handles, Towel Bar/Handle Combinations and Grab Bars at [crlaurence.com](http://crlaurence.com)

## BM Series Back-to-Back Tubular Towel Bar With Metal Washers

- Decorative Metal Washers Also Serve to Cover Any Defect in Hole in Glass

### SPECIFICATIONS:

**Material:** 3/4" (19 mm) Diameter Brass Tubing (1.5 mil thick);  
1-1/4" (32 mm) Diameter Metal Washers  
**Glass Thickness Range:** 1/4" to 1/2" (6 to 12 mm)  
**Hole Diameter Required:** 1/2" (12 mm)  
**Center-to-Center Hole Spacing:** 20" (508 mm)

**MORE FINISHES**  
[crlaurence.com](http://crlaurence.com)

1/4" to 1/2"



MODEL BM20X20

## BM Series Back-to-Back Tubular Towel Bar Without Metal Washers

- No Metal Washers Creates a Sleek, Continuous Profile

### SPECIFICATIONS:

**Material:** 3/4" (19 mm) Diameter Brass Tubing (1.5 mil thick)  
**Glass Thickness Range:** 1/4" to 1/2" (6 to 12 mm)  
**Hole Diameter Required:** 1/2" (12 mm)  
**Center-to-Center Hole Spacing:** 16" (406 mm)

1/4" to 1/2"



MODEL BMNW16X16

## BPD Series Back-to-Back Solid Brass Constructed Towel Bar

- No Metal Washer Creates a Sleek, Continuous Profile

### SPECIFICATIONS:

**Material:** 3/4" (19 mm) Diameter Solid Brass  
**Glass Thickness Range:** 1/4" to 1/2" (6 to 12 mm)  
**Hole Diameter Required:** 1/2" (12 mm)  
**Center-to-Center Hole Spacing:** 18" (457 mm)

1/4" to 1/2"



MODEL BPD18

## Rectangular Heavy-Duty Solid Brass Towel Bar

- Unique Rectangular Appearance
- Solid Brass Construction

### SPECIFICATIONS:

**Material:** Solid Brass Material  
**Glass Thickness Range:** 3/8" to 1/2" (10 to 12 mm)  
**Hole Diameter Required:** 1/2" (12 mm)  
**Center-to-Center Hole Spacing:** 18" (457 mm)

3/8" to 1/2"



MODEL HDTB1

Our Polished Chrome Heavy-Duty Rectangular Towel Bar puts the emphasis on strong and sturdy. The solid brass constructed, polished chrome plated towel bar says "notice me" when mounted on a beautiful frameless shower enclosure.

## 1-1/2" Diameter Brushed Stainless Steel Grab Bar

- T304 18 Gauge Stainless Steel
- Exceeds A.D.A., VA, FHA, and Other Federal, State, and Local Building Codes

### SPECIFICATIONS:

**Material:** 1-1/2" (38 mm) Diameter Stainless Steel  
**Finish:** Brushed Stainless  
**Length:** 18" (457 mm) Center-to-Center

**MORE SIZES**  
[crlaurence.com](http://crlaurence.com)



MODEL GA3SF18

1-1/2" (38 mm) Diameter Stainless Steel Grab Bar has a #4 brushed satin finish. When installed properly, this Grab Bar can support loads in excess of 1300 lbs. (589 kg). Wall clearance is 1-1/2" (38 mm) from the wall to inside edge of tubing. This exceeds A.D.A., VA, FHA, and other federal, state, and local building codes. Mount only to a wall, not glass.

# CRL GLASS CLAMPS AND SUPPORT BAR BRACKETS

Go to [crlaurence.com/shower-hinges](http://crlaurence.com/shower-hinges) for Available Finishes

## "Y" Inline Square Corner Style Glass Clamp

3/8" to 1/2"



- Used as a "Y" Clamp Along Edge of Step Wall



### SPECIFICATIONS:

Material: Solid Brass  
Glass Thickness Range: 3/8" to 1/2" (10 to 12 mm)  
Glass Fabrication Required  
Includes: Mounting Screws and Gaskets


MODEL SGC182

## "Y" Inline Beveled Style Glass Clamp

3/8" to 1/2"



- Used as a "Y" Clamp Along Edge of Step Wall



### SPECIFICATIONS:

Material: Solid Brass  
Glass Thickness Range: 3/8" to 1/2" (10 to 12 mm)  
Glass Fabrication Required  
Includes: Mounting Screws and Gaskets

MODEL BGC182

## Open Face 90 Degree Glass-to-Glass Square Style Glass Clamp

3/8" to 1/2"



- Open Face Design Provides Improved Aesthetics
- Used for Joining 90 Degree Fixed Glass Panels



### SPECIFICATIONS:

Material: Solid Brass  
Glass Thickness Range: 3/8" to 1/2" (10 to 12 mm)  
Glass Fabrication Required  
Includes: Gaskets

MODEL SGC0F90

## Riviera Series Fixed Panel Glass Clamp

5/16" to 3/8"



- Matching Style to Riviera Series Hinges
- Mounts to Floor, Ceiling, or Wall



### SPECIFICATIONS:

Material: Solid Brass  
Glass Thickness Range: 5/16" to 3/8" (8 to 10 mm)  
Glass Fabrication Required  
Includes: Gaskets

MODEL R1V79

## Adjustable Support Bar Bracket

- Swivels to Accommodate Various Angles
- For Use Only With 1/4" or 5/16" (6 or 8 mm) Thick Tempered Glass



The Adjustable Support Bar Bracket is for use with only 1/4" or 5/16" (6 or 8 mm) thick tempered glass thicknesses. It is installed at the top of the glass and swivels to accommodate various angles. Simply secure to the end of a S1, S2 or S80 length Support Bar.

MODEL S6ADJ

## Wall Mount Support Bar Top Fitting

- Used to Stabilize Shower Enclosures Not Going to the Ceiling
- Use With S1, S2 or S80 Support Bars



The S14 Wall Mount Top Fitting is for use with our entire line of Support Bar Accessories. It will fit on the end of S1, S2 or S80 Support Bars to assist in stabilizing shower enclosures that do not go to the ceiling.

MODEL S14

## Support Bar T-Bracket

- Allows Three-Way Connection
- Attaches to S1, S2 or S80 Bar



Our Support Bar T-Bracket can be used to conveniently make a 3-way connection to support fixed panels of glass. The three openings of the T-Bracket accept our S1, S2 or S80 Support Bars.

MODEL SUPT

## Squared Cornered Support Bar Brackets

- Fit SQ39 and SQ59 Bars
- Bracket Fits on Top Edge of Fixed Panel



This Square Cornered Support Bar Bracket mounts on top of a fixed panel of glass with the attached support bar extending in an upward direction to the ceiling. Use with Cat. No.'s SQ39 or SQ59 Bars. Wall mounting bracket is ordered separately for mounting to the ceiling.

MODEL SQ910  
For 3/8" to 1/2"  
(10 to 12 mm)

MODEL SQ9  
For 1/4" to 5/16"  
(6 to 8 mm)


## U-Channel for Recessed Applications

- Ideal for Recessing Glass and Creating the "All-Glass" Appearance
- Top of Channel Angled to Assist With Water Deflection
- Top Lip Helps Cover Edge of Tile
- Models for 3/8" or 1/2" (10 or 12 mm) Tempered Glass

**MODEL SDCF38**  
For 3/8" (10 mm)  
Tempered Glass



**MODEL SDCF12**  
For 1/2" (12 mm)  
Tempered Glass



This U-Channel is the ideal selection for recessing into the floor, wall, or ceiling to provide the frameless "all-glass" appearance. The top lip of the U-Channel is angled to deflect the water away and conceal the edge of the tile. Glass is wet glazed into the Channel. 98" (2.49 m) stock lengths are available for 3/8" or 1/2" (10 or 12 mm) tempered glass.

go to [crlaurence.com](http://crlaurence.com) for complete dimensions

## Door Stop

- Ideal for Use With CRL Hydroslide Bifold System




The Door Stop for CRL's Hydroslide Bifold Hinge System will protect the shower door from closing too far and damaging the door. The solid brass constructed Door Stop is dimensioned to accept 3/8" and 5/16" (10 and 8 mm) thick tempered glass when used in conjunction with our Hydroslide Bifold Hinges (HYDH037 and HYDH180). No glass fabrication is required.

**MODEL DSBF1**

## Adjustable Curved Shower Rod

- Adjustable 54" to 72" (1.37 to 1.83 m) Length to Accommodate Most Any Shower Enclosure
- Curved Rod Provides More Shower Space



Our Adjustable Curved Shower Rods will provide more space in the shower enclosure. The 1" (25 mm) diameter rods come in a choice of durable stainless steel construction (polished and brushed), or economical zinc construction in five popular finishes (polished chrome, polished brass, brushed nickel, oil rubbed bronze, and satin chrome). Mounting hardware is included in each box to assist with easy installation. Custom finishes are available upon request.

**MODEL ASR1**

go to [crlaurence.com/shower-seals](http://crlaurence.com/shower-seals) to view our complete line of shower door wipes and seals

## "h" Jamb With Hard Leg

- Popular 180 Degree Inline Seal
- Snaps Onto Fixed Panel
- For 3/8" (10 mm) Thick Glass

98" (2.49 m)  
Stock Length



**CAT. NO.**  
**P10MMHJ**

## U-Shape Polycarbonate With 90 Degree Leg

- Most Commonly Used With CRL Essence Sliding System
- Sealing Fin is 13/16" (21 mm) Long
- For 1/2" (12 mm) Thick Glass

98" (2.49 m)  
Stock Length



**CAT. NO.**  
**PC1200**

## Hydroslide Bottom Sweep

- Commonly Used With Our Hydroslide Sliding System
- For 5/16" or 3/8" (8 or 10 mm) Thick Glass

Fits in both our HYD08 and HYD09 Sliding Door Guides, minimizing water leakage

**CAT. NO.**  
**HYD98**



98" (2.49 m)  
Stock Length

Go to [crlaurence.com/shower-sliders](http://crlaurence.com/shower-sliders) to View Our Complete Line of Sliding Systems

## Essence Series Rolling Shower Door System (With Header)

- Header System Allows for Use of 3/8" or 1/2" (10 or 12 mm) Thick Tempered Glass (Not Included)
- Bottom Rolling System has Integrated Height Adjustment

3/8" to 1/2"



### BASIC 180 DEGREE KIT INCLUDES THE FOLLOWING:

- One - 60" (1.52 m) or 84" (2.13 m) Header
- One - Pack of Two BWB2 Header Mounting Brackets
- Two - Bottom Rollers
- One - Spanner Wrench for Roller Adjustment
- One - Top Guide/Roller
- One - 60" (1.52 m) or 84" (2.13 m) Bottom Track
- One - 98" (2.49 m) U-Channel
- One - 98" (2.49 m) Plastic L-Seal
- Two - 180 Degree Fixed Glass Fittings
- One - SDCEC12 or SDCEC38 End Cap for Channel
- One - 1/16" (1.6 mm) Neoprene Setting Block

**NOTE:** Handle or Knob and Other Accessories Sold Separately



Rounded Roller Style



Square Corner Roller Style



POLISHED CHROME CAT. NO.	BRUSHED NICKEL CAT. NO.	POLISHED BRASS CAT. NO.	OIL RUBBED BRONZE CAT. NO.	DESCRIPTION
ESS560CH	ESS560BN	ESS560BR	ESS5600RB	60" (1.52 m) Basic 180° Rounded Style Essence Kit With Header
ESS584CH	ESS584BN	ESS584BR	ESS5840RB	84" (2.13 m) Basic 180° Rounded Style Essence Kit With Header
ESS760CH	ESS760BN	ESS760BR	ESS7600RB	60" (1.52 m) Basic 180° Square Style Essence Kit With Header
ESS784CH	ESS784BN	ESS784BR	ESS7840RB	84" (2.13 m) Basic 180° Square Style Essence Kit With Header
BR4CH	BR4BN	BR4BR	BR40RB	Replacement Rounded Style Bottom Roller
SR4CH	SR4BN	SR4BR	SR40RB	Replacement Square Style Bottom Roller
HTG4BN	HTG4BN	HTG4BN	HTG4BN	Top Guide Roller (Brushed Nickel Only - Not Exposed)
FGF4CH	FGF4BN	FGF4BR	FGF40RB	Replacement 180 Degree Fixed Glass Fitting
90RFCH	90RFBN	90RFBR	90RF0RB	90 Degree Return Fitting
ESSH60CH	ESSH60BN	ESSH60BR	ESSH600RB	60" (1.52 m) Replacement Header/Header Cover
ESSH84CH	ESSH84BN	ESSH84BR	ESSH840RB	84" (2.13 m) Replacement Header/Header Cover
BT484CH	BT484BN	BT484BR	BT4840RB	84" (2.13 m) Replacement Bottom Track
SDCD38BA	SDCD38BN	SDCD38BGA	SDCD380RB	98" (2.49 m) Replacement U-Channel for 3/8" (10 mm)
SDCD12BA	SDCD12BN	SDCD12BGA	SDCD120RB	98" (2.49 m) Replacement U-Channel for 1/2" (12 mm)
DK98L	DK98L	DK98L	DK98L	98" (2.49 m) Replacement Clear Plastic L-Seal

### SPECIFICATIONS:

- Glass Thickness:** 3/8" or 1/2" (10 or 12 mm) Thick Tempered Safety Glass (Not Included)
- Material:** Extrusions (Aluminum); Bottom Rollers and Top Guide (Solid Brass); L-Jamb (Polycarbonate)
- Recommended Maximum Slider Sizes:** 3/8" (10 mm) Glass: 34" (864 mm) Wide or 109 Pounds (49 kg); 1/2" (12 mm) Glass: 34" (864 mm) Wide or 127 Pounds (58 kg)
- Basic Kit Fabrication:** Notch Required for Bottom Rollers, Holes Required for Top Guide; Holes Required for 180 Degree and 90 Degree Thru Glass Fittings. (see [crlaurence.com](http://crlaurence.com) for details)

### FINISHES:



go to [crlaurence.com](http://crlaurence.com) for available finishes

## Decorative Posters

- Show Your Customers Beautiful Showers and Tubs Created With CRL Frameless Shower Hardware and a Little Imagination
- Large 24" (610 mm) Wide x 36" (914 mm) High Studio Quality Posters Can Be Displayed Anywhere in Their Protective Clear Sleeves
- Visit [crlaurence.com](http://crlaurence.com) to See All Available Decorative Posters
- New Posters Added Regularly



To view larger images and new additions of our Decorative Posters, please visit [crlaurence.com/posters](http://crlaurence.com/posters)

## Sliding Door Guide

CAT. NO.	FINISH
HYD08CH	Polished Chrome
HYD08BR	Polished Brass
HYD08BN	Brushed Nickel
HYD080RB	Oil Rubbed Bronze

Minimum order: 1 each.




Allows the use of our HYD98 Bottom Sweep (see page 7).

## Sliding Door Offset Guide

CAT. NO.	FINISH
HYD09CH	Polished Chrome
HYD09BR	Polished Brass
HYD09BN	Brushed Nickel
HYD090RB	Oil Rubbed Bronze

Minimum order: 1 each.



Allows the use of our HYD98 Bottom Sweep (see page 7). Offset to assist with uneven curb conditions.