

CRL GLASS PROTECTORS AND SHIPPING PADS

For Pricing Visit crlaurence.com or Call Us Toll Free at the Phone Numbers Shown on the Back Cover

CRL Sponge Rubber Shipping Pads

- Economical and Easy to Use
- Leave No Residue When Removed
- For Storing and Transporting Glass
- Now in 1/8" (3.2 mm) and 1/4" (6.3 mm) Thickness

Developed for the tempering industry for use on hot glass during processing, and made of heavy-duty composition rubber, these CRL Shipping Pads have a special adhesive that leaves no residue when removed from the glass. They are excellent to use when transporting or storing glass to prevent surface scratches and breakage. Application is simple - just peel from the release paper roll and stick them to the glass. No special equipment, tools or solvents are needed to remove them. Pre-cut pads are available in two ways: on rolls of 1,000; in bulk quantities of 5,000 each of the 3/4" (19 mm) size, and 10,000 each of the 1/2" (12.7 mm) size.



CAT. NO.	PAD SIZE	THICKNESS	PADS/ROLL
SP1412	1/2" (12.7 mm) Square	1/4" (6.3 mm)	1,000
SP1412B	1/2" (12.7 mm) Square	1/4" (6.3 mm)	10,000
SP1834	3/4" (19 mm) Square	1/8" (3.2 mm)	1,000
SP1834B	3/4" (19 mm) Square	1/8" (3.2 mm)	25,000
SP1434	3/4" (19 mm) Square	1/4" (6.3 mm)	1,000
SP1434B	3/4" (19 mm) Square	1/4" (6.3 mm)	5,000

Minimum order: 1 roll. Sizes can be combined for quantity pricing.



CRL Super-Duty Shipping Pads

- Used by Aluminum Window and Door Fabricators
- Handles Heavy Loads and Shock
- Easy-to-See Light Yellow Color

These CRL Super-Duty Shipping Pads are used by aluminum window and door fabricators to support and separate finished units during transport and storage. The highly condensed white troc ellen foam compresses slightly under load, and has great capacity to handle shock and heavy loads. The adhesive coating sticks tight in all climates, yet leaves no residue or discoloration on metal surfaces when removed, even after months of storage. CRL Super-Duty Shipping Pads are die-cut on sheets of release paper, and peel off easily for application, even in high-production situations. Standard thicknesses are 1/4" and 1/2" (6.3 and 12.7 mm), and all sizes are packed in boxes that will ship U.P.S.



CAT. NO.	PAD SIZE	THICKNESS	PADS/ROLL
NSP1411	1" x 1" (25.4 x 25.4 mm)	1/4" (6.3 mm)	12,096
NSP141515	1-1/2" x 1-1/2" (38.1 x 38.1 mm)	1/4" (6.3 mm)	5,376
NSP14152	1-1/2" x 2" (38.1 x 50.8 mm)	1/4" (6.3 mm)	4,032
NSP1422	2" x 2" (50.8 x 50.8 mm)	1/4" (6.3 mm)	3,024
NSP1211	1" x 1" (25.4 x 25.4 mm)	1/2" (12.7 mm)	6,048
NSP121515	1-1/2" x 1-1/2" (38.1 x 38.1 mm)	1/2" (12.7 mm)	2,668

Minimum order: 1 box. Sizes can be combined for quantity pricing.



C.R. LAURENCE COMPANY

crlaurence.com | usalum.com

242K | crlaurence.ca crlaurence.com.au crlaurence.co.uk crlaurence.de crlaurence.eu