

CRL HAND HELD VACUUM LIFTERS

For Pricing Visit crlaurence.com or Call Us Toll Free at the Phone Numbers Shown on the Back Cover

CRL Sure-Grip 8" Vacuum Lifter

- Greatest Lifting Capacity of Any 8" (203 mm) Pump Activated Vacuum Lifter
- Meets CE and GS Conformance
- Eligible for Exchange Program

This Sure-Grip Vacuum Lifter is manufactured by C.R. Laurence Co. in Australia. The state-of-the-art design of the S338 offers unique features, setting it apart from other 8" (203 mm) pump-activated vacuum lifters. Minimum order is one each.



• Superior Comfort and Grip

The ergonomically designed shape of the S338's soft contoured Sure-Grip provides a comfortable hold during lifting compared to straight, hard handles. Thousands of micro-pads are aligned in the handle material to provide greater slip resistance during lifts for yet another measure of safety.



• Superior Release

Extremely fast release from the work surface is attributed to a combination of the S338's uniquely designed rubber pad and new, specially designed relief valve placed safely inside the valve's guard.



• Excellent Attachment

The S338 has a wide 1/2" (12 mm) lip for fast attachment to glass and other non-porous, flat surfaces. This is also a major factor in the S338's 150 pound (68 kg) lifting capacity with a 3.3 safety factor. Protective carrying case included.

Lifting Capacity
150 Lbs. (68 kg)

CAT. NO. S338

• Convenient Vacuum Indicator

The pump's plunger has a red indicator line to show the vacuum level when the lifter is in use. When the lifter is properly attached to the load's surface, the red line will be hidden inside the pump. Should the red line become visible during a lift, set down the load and re-pump until red line is again hidden.



• Superior "Press and Pump" Attachment Feature

The special rubber pad lip design enables one hand attachment of the vacuum lifter with only light pressure, allowing you to pump with the fingers of the same hand holding the lifter. Your other hand is free to secure your position for greater safety, especially important when you have the need to reposition your lifter on large vertical glass lites.



• Superior Lifting Capacity Performance

Third party independent lab tests rate the S338 at 150 pounds (68 kg) with a big 3.3 safety factor.



C.R. LAURENCE COMPANY

crlaurence.com | usalum.com

202K | crlaurence.ca crlaurence.com.au crlaurence.co.uk crlaurence.de crlaurence.eu