MAGIC SWITCH: MS21H

SHORT-RANGE TOUCHLESS ACTUATOR
































DESCRIPTION

BEA's state-of-the-art MS21 is the Industry's first low-profile touchless actuator plate utilizing unique capacitive technology for the activation of automatic doors.

The hands-free MS21 includes a stainless steel faceplate and an illuminated LED mounting ring for unparalleled durability, visibility and convenience.

The MS21 blends form with function into an aesthetically pleasing design that is ideal for healthcare facilities, labs, pharmaceutical, clean rooms, washdown areas and a variety of other applications. The MS21 helps reduce the spread of germs and bacteria.

Innovative features include a short-range adjustable detection zone, visual and audible alerts, NEMA 4 rated enclosure, backlit LED and a variety of faceplate design options.

FEATURES & BENEFITS

- Short range detection zone reduces unwanted activations
- LED illuminated mounting ring increases visibility
- Stainless steel faceplate is ideal for harsh environments
- Low profile, beveled design reduces accidental damage
- Various faceplate graphic options available
- Adjustable audible alerts, visual alerts and touchless detections zones
- NEMA 4 enclosure
- Inter-operates with all automatic door control makes and models



BEA, Inc. **RIDC Park West** 100 Enterprise Drive

Customer Service: 800.523.2462 Technical Support: 800.407.4545

Pittsburgh, PA 15275-1213 www.BEAinc.com


APPLICATIONS








DIMENSIONAL DRAWINGS



MS21HR Series



MS21HS Series

TECHNICAL SPECIFICATIONS **Technology Type** Capacitance **Detection Mode** Proximity 12 to 24 VAC / VDC; ±10% **Supply Voltage Current Consumption** 37 mA **Temperature Range** -20°F to +120°F NEMA 4 / IP65 **Degree of Protection** Maximum detection zone of up to 4 inches Detection zone is dependent on: **Detection Zone** Size (area) of an object | orientation of an object | speed of an object | environmental conditions 1 Form A solid-state relay; 0.4 A, 60 VAC / Relay VDC (Max.) 6 inches (5 conductor) **Cable Length** Stainless Steel (faceplate) Material Clear Polycarbonate (Mounting Ring, Backplate and Enclosure)

MS21H SERIES



10MS21HR1 6" ROUND, TEXT & LOGO



10MS21HR 6" ROUND, TEXT ONLY



10MS21HRLL 6" ROUND, LOGO ONLY



10MS21HS1 4.75" SQUARE, TEXT & LOGO



10MS21HS 4.75" SQUARE, **TEXT ONLY**



10MS21HSLL 4.75" SQUARE, LOGO ONLY

www.BEAinc.com © 2015 BEA, Inc. All rights reserved

MAGIC SWITCH: MS21H SHORT-RANGE TOUCHLESS ACTUATOR



Customer Service: 800.523.2462 Pittsburgh, PA 15275-1213 Technical Support: 800.407.4545



