

EGRESS SWITCHES/SUPERVISED ENTRY

All models are UL Listed and Internationally approved. The 200 and 300 Series heavy-duty key switches and push buttons are ideal with any electrical locking device to provide security for both restricted areas and supervised entrances.

200 Series Key Switches



Type	Momentary or Alternating with 22 GA pigtail leads.
Ratings	Switch ratings – 6 A at 28 VDC or 250 VAC.
Cylinder	Specify 1-1/8" or 1-1/4" Mortise cylinder with any cam. Adjustable switch position for cylinder compatibility. Cylinder not supplied.
LED	Red or Green bi-color LED to monitor status of the alternating key switch. 22 gage 6" pigtail leads. Draws 40 mA at 12 VDC or 20 mA at 24 VDC.
Security	1/4" thick solid aluminum escutcheon, recessed for key cylinder, and supplied with spanner head screws.
Ordering Information	
200 x 28/313	Momentary; SPDT 3.0" standard width Key Switch.
200N x 28/313	Momentary; SPDT 1.75" narrow width Key Switch.
210 x 28/313	Alternating; SPDT 3.0" standard width Key Switch.
210N x 28/313	Alternating; SPDT 1.75" narrow width Key Switch.
Options	
KTD-1	Pneumatic Time Delay, adj. from 1 to 320 seconds, DSPST.
KTD-2	Electronic Time Delay adj. from 1 to 60 seconds; 12 or 24 VDC, SPDT. (KTD-2 uses a CY-1/2 3" x 2" switch box).
LED	Bi-color Red or Green "ON" indicator. Field-selectable color.
WR	Weather Resistant Escutcheon Plate.