

842 & 942 Non-Handed Automatic Flush Bolts

No. 842 for Metal Doors
Fire-Rated 3 Hours



No. 942 for Wood Doors
Fire-Rated 1½ Hours



Automatic flush bolts are installed in the top and bottom of the inactive door. Closing the active door automatically extends both top and bottom bolts $\frac{3}{4}$ " into frame and sill strikes, locking inactive door. Opening the active door retracts top and bottom bolts, releasing the inactive door. Manufactured and assembled in Dexter, Michigan.

Listings

UL Listed, No. R7912, ADA Compliant
Cycle tested (500,000) under UL supervision
UL Certified to ANSI/BHMA 156.3-2008, Grade 1, Type 25
Patent Nos. 4611840, 4005886

Override Feature

The override spring prevents damage to doors or bolts should the bolt head be unable to extend into the top or bottom strike.

Low Closing Force

Patented free floating cams require less than 5 lbs. closing force of the active door to extend both top and bottom bolts.

Adjustable Bolt Head Rods

Bolts can be vertically adjusted for unusual clearances, floor or head conditions. An adjustment of $1\frac{1}{4}$ " is available for the 842 Series and $\frac{1}{2}$ " for the 942 Series.

Low Inventory

Trim Packages can be ordered separately to reduce inventory levels, which consist of bolt cover plates, strikes, and screws.

Stock Finishes

US Standard	US3, US4, US10, US10B, US26, US26D, US32, US32D
BHMA Standard	605, 606, 612, 613, 625, 626, 629, 630