

845 & 945 Non-Handed Self-Latching Flush Bolts

No. 845 for Metal Doors
Fire-Rated 3 Hours

No. 805
Self-Latching Bolt
(Top Bolt Only)



No. 840
Automatic Flush Bolt

No. 945 for Wood Doors
Fire-Rated 1½ Hours

No. 905
Self-Latching Bolt
(Top Bolt Only)



No. 940
Automatic Flush Bolt



Self-Latching Flush Bolts will engage the curved frame lip strike as the inactive door closes, locking the inactive door. The top bolt will remain locked until the plunger is depressed on the face of bolt. The bottom bolt, an Automatic Flush Bolt, will engage the sill and frame strike only when the active door is closed, and will be released when the active door is opened. Manufactured and assembled in Dexter, Michigan.

Listings

UL Listed, No. R9600, ADA Compliant
Conforms to ANSI/BHMA 156.3-2008, Type 27
Patent Nos. 4611840, 4005886

Override Feature

The override spring prevents damage to doors or bolts should the bolt head be unable to extend into the top or bottom strike.

Low Closing Force

Patented free floating cams require less than 5 lbs. closing force of the active door to extend both top and bottom bolts.

Adjustable Bolt Head Rods

Bolts can be vertically adjusted for unusual clearances, floor or head conditions. An adjustment of 1¼" is available for the 845 Series and ½" for the 945 Series.

Low Inventory

Trim Packages can be ordered separately to reduce inventory levels, which consist of bolt cover plates, strikes, and screws.

Stock Finishes

US Standard	US3, US4, US10, US10B, US26, US26D, US32, US32D
BHMA Standard	605, 606, 612, 613, 625, 626, 629, 630