

THRESHOLDS

1/2" (12.7mm) Rise Thresholds

1/2" (12.7mm)

4" (102mm)

1-1/2 HR
Intertek RATING
.518 lbs./ft. (.771 kg/m)

DS400A

Extruded aluminum mill finish

DS400D

Bronze anodized

1/2" (12.7mm)

5" (127mm)

1-1/2 HR
Intertek RATING
.493 lbs./ft. (.734 kg/m)

DS95A

Extruded aluminum mill finish

1/2" (12.7mm)

5" (127mm)

1-1/2 HR
Intertek RATING
.606 lbs./ft. (.902 kg/m)

DS500A

Extruded aluminum mill finish

DS500D

Bronze anodized

1/2" (12.7mm)

5" (127mm)

1-1/2 HR
Intertek RATING
.602 lbs./ft. (.877 kg/m)

DS505A

Extruded aluminum mill finish

1/2" (12.7mm)

6" (152mm)

1-1/2 HR
Intertek RATING
.747 lbs./ft. (1.112 kg/m)

DS600A

Extruded aluminum mill finish

DS600D

Bronze anodized

1/2" (12.7mm)

7" (178mm)

1-1/2 HR
Intertek RATING
.913 lbs./ft. (1.359 kg/m)

DS700A

Extruded aluminum mill finish

DS700D

Bronze anodized

1/2" (12.7mm)

8" (203mm)
product not shown full width

1-1/2 HR
Intertek RATING
1.158 lbs./ft. (1.724 kg/m)

DS800A

Extruded aluminum mill finish

DS800D

Bronze anodized

Thresholds on this page are supplied with punched countersunk holes with screws and plugs and are only available in the following NET lengths (except as noted):

36-1/2"	927mm
49"	1245mm
73"	1854mm
110"	2794mm
147"	3734mm

8

FULL SCALE EXCEPT AS NOTED. SEE PAGE 6 FOR SYMBOL DETAIL | DraftSeal Product Catalogue | © Copyright DS Group® & DraftSeal®