


DRAFTSEAL

DSS44 / DSS55

DOOR GASKET SEAL

SELF ADHESIVE JAMB WEATHERSTRIP



NO SCALE

DSS55W17	DSS44W17 , WHITE, 17FT
DSS55W20	DSS44W20 , WHITE, 20FT
DSS55W21	DSS44W21 , WHITE, 21FT
DSS55W25	DSS44W25 , WHITE, 25FT

DSS55D17	DSS44D17 , BRONZE, 17FT
DSS55D20	DSS44D20 , BRONZE, 20FT
DSS55D21	DSS44D21 , BRONZE, 21FT
DSS55D25	DSS44D25 , BRONZE, 25FT

ALSO AVAILABLE IN 204FT BULK COILS

DSS44 / DSS55

INSTALLATION INSTRUCTIONS

WARNING: IMPORTANT INFORMATION FOLLOWS

APPLICATION TEMPERATURE

The adhesive on SEALPRENE will have the best end use high and low temperature adhesion if installed to a clean dry frame between 65F-80F. For proper performance do not install on a frame at less than 50F or more than 100F

50F=10C 80F=27C
65F=18F 100F=39C

SURFACE PREPERATION:

Surface should be clean, dry and free of dust, grease, oil or solvents. Paint must be applied 30 days prior to application of gasket (quick dry primers often dry just on or before contact leaving a powdered, improperly adhered paint surface which responds like dust preventing good adhesion to self adhesive backing). If applied to a wood frame the painted or finished surface must be non-porous and smooth.

SURFACE APPLICATION

Surfaces may be cleaned with alcohol wipes included to remove any dirt, grease or solvent residue. Wipe away detergent with a clean cloth and allow frame to dry before installing.

INSTALLATION

A.

Remove approximately 36" of paper backing from the SEALPRENE GASKET strip-being careful not to touch with dirty or sweaty hands or drag adhesive in dust or dirt.

B.

Position SEALPRENE in rabbet of stop and press in place without stretching the SEALPRENE. Press each inch of length to activate all of the adhesive to the frame.

C.

Remove next 36" of paper backing repeating step B until entire length for head or jamb is installed. Do not install as one continuous piece-cut material at corners where head and jambs meet.

Product listed by this by this symbol are labeled as GASKETING MATERIAL FOR USE ON LISTED STEEL FRAMES AND LISTED SWINGING TYPE FIRE DOORS OF THE HOLLOW METAL OR STEEL COVERED COMPOSITE TYPE RATED UP TO 1 ½ HOURS. These products have been listed and labeled as a result of testing done by Warnock Hersey certifying that these gasketing products do not adversely affect the fire resistance of the door frame. Products are regularly checked under the follow-up factory inspection and certification service for manufacturing compliance service for manufacturing compliance with Warnock Hersey specifications. Contact A.K. Draftseal Ltd. For further information.

WARNOCK HERSEY



Tested in accordance with CAN/ULC S104,
ASTM-E-152, CFSM, 43.7, NFPA 252, UBC
7-2-1994 (formerly UBC 43-2-1991), UL 10(b)
LISTED FOR CANADA AND USA

WARNING: INCORRECT SURFACE PREPARATION MAY RESULT IN INCOMPLETE SETTING OF ADHESIVE AND SEPERATION OF SEALPRENE GASKET FROM THE FRAME. It is not recommended that installation of adhesive backed materials take place after construction is completed, flooring material has been installed and the final cleaning has taken place.