



Eaton 9SX 9SX3000 3000VA UPS

0 reviews

The Eaton 9SX UPS provides reliable double-conversion online power you expect from a 9-series UPS in a convenient and compact tower. The 9SX UPS is ideal for light industrial, automations and other mission critical IT applications where space is limited, but premium power reliability is essential.

Features With Display

Type On-line

VA Rating 3,000 VA

Wattage 2,700 watts

General

Device Type UPS - external

Color Black

Power Device

UPS Technology On-line

Input Voltage AC 100/110/120/125 V

Input Voltage Range AC 100 - 138 V

Input Voltage Range (Adjustable) AC 60 - 144 V

Frequency Provided 50/60 Hz

Frequency Required 40 - 70 Hz

Input Connectors 1 x power NEMA L5-30P

Power Output Connectors Details 4 x power NEMA 5-20R 1 x power NEMA L5-30R

Output Voltage AC 100/110/120/125 V 50/60 Hz

Power Capacity 2700 Watt / 3000 VA

Output Waveform Sinewave

Surge Suppression Yes

Efficiency 89%

Power Factor (PF) 0.9

Battery

Technology Lead acid

Features Sealed

Networking

Remote Management Interface RS-232, USB

Expansion / Connectivity

Interfaces 1 x management (RS-232) - 9 pin D-Sub (DB-9) 1 x management (USB) - 4 pin USB Type B

Expansion Slots 1 (total) / 1 (free) x expansion slot

Miscellaneous

Cables Included Serial cable - external - 6 ft USB cable - external - 6 ft Power cable 8 ft

Features Advance Battery Management (ABM), LCD display, hot-swappable batteries, 3-stage charging, double conversion

Compliant Standards FCC, cULus

Software / System Requirements

Software Included Intelligent Power Manager

Manufacturer Warranty

Service & Support Limited warranty - 2 years Limited warranty - batteries - 2 years

Environmental Parameters

Min Operating Temperature	32 °F
Max Operating Temperature	104 °F
Humidity Range Operating	0 - 96% (non-condensing)
Sound Emission	50 dBA

Dimensions & Weight

Width	8.4 in
Depth	16.2 in
Height	13.6 in
Weight	73.63 lbs