Eaton ELSPSTWC

Catalog Number: ELSPSTWC

Eaton Eluxa high fidelity speaker strobe, LED, ceiling, white, FIRE, clear lens, 15/30/75/110/150/177 cd, 25/70V, indoor

General specifications



UPC Product Height

786697009679 3.64 in

Product Diameter Product Weight

6.2 in 1.86 lb

Warranty Compliances
3 year Not Applicable

Certifications

Contact Manufacturer





Product specifications

Sound level (dBA)

75/79/82/85/87

Type of speaker

High fidelity

Housing material

Plastic

Lamp type

LED

Mounting Method

Ceiling

Current draw (DC)

0.022

0.030

0.060

0.086

0.125

0.185

Frequency range - min

300 Hz

Lettering

FIRE

Taps (Selectable)

1/8, 1/4, 1/2, 1, 2

Indoor/outdoor

Indoor

Candela settings

15 cd

30 cd

75 cd

95 cd

150 cd

177 cd

Type

Speaker strobe

Voltage

24 V

25 V

70 V

Resources

Brochures

Eluxa family brochure

Eluxa product cross reference

Catalogs

Wheelock life safety notification appliances catalog CA450001EN

Drawings

Eluxa speaker strobe ceiling drawing

Eluxa speaker strobe wall drawing

Installation instructions

Eluxa speaker wall install sheet P85757

Eluxa speaker ceiling install sheet P85758

Selling policy and T&Cs

Eluxa UL listing

Specifications and datasheets

Eaton Specification Sheet - ELSPSTWC

Technical data sheets

Eluxa high fidelity amber lens speaker strobes data sheet

Eluxa high fidelity speaker data sheet

wheelock-mounting-accessories-data-sheet

Housing color

White

Lens color

Clear

Lens material

Lexan

Operating Temperature

32°F to 122°F (0°C to 50°C)

Compliance and standards

UL

ULC

FCC

Frequency range - max

8000 Hz



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia