



I. Product Description

Gasket Remover is a solvent-based, high strength cleaner that helps remove baked-on fiber gaskets, gasket adhesives and sealants. It quickly dissolves and aids in the removal of paints, lacquers, adhesives and varnishes. **Gasket Remover** contains no methylene chloride.

II. Applications

Recommended for the effective removal of conventional and formed-in-place gaskets on motors, pumps and flanges. Aids in dissolution and removal of paints, lacquers, adhesives and varnishes. Removes graffiti from metal and stone.

III. Features & Benefits

- **Works Quickly.** Softens and eases removal of gaskets, gasket cements and sealants.
- **Loosens Carbon Deposits.**
- **Protects Equipment Surfaces.** Reduces the need for excessive scraping.
- **Excellent Paint, Varnish and Graffiti Remover.** Aggressive cleaner works efficiently.
- **Contains No Methylene Chloride.**
- **M.S.D.[L.]™-Material Safety Data Label.** Provides instant access to current safety information should an accident or OSHA inspection occur. Helps comply with **OSHA Hazard Communications Standard 29 CFR 1910.1200.**

IV. Physical Properties without propellant

Flash Point	0° F (TCC)	Solubility	Neg. in water
Odor	Solvent odor	VOC %	28.2%
Appearance	Viscous, opaque liquid	Specific Gravity	0.9000
Vapor Density	>air	Propellant	Hydrocarbon
Sara Title III, Sect. 313 Chemicals	Yes		
Prop 65	Yes		
% VOC	28% by weight		
VOC Content (Fed)	277 g/L		

V. Specifications and Approvals

- Meets 1998 USDA guidelines for use in meat and poultry plants.

VI. Performance Characteristics

ASTM D-1130 (KB Value)	136
------------------------	-----

VII. Directions

- Wear eye protection and rubber gloves or other non-porous hand protection.
- Protect painted surfaces from overspray, as product will dissolve paint.
- Gasket removal: spray liberal coating on gasket and allow to set for 5 - 10 minutes. Remove with putty knife.
- Paint and graffiti removal: spray liberal coating on painted surface. Allow to dry and brush with a stiff bristled brush.
- Adhesive removal: apply liberal coating and allow to work for 2 - 3 minutes. Wipe with rag or wiper. Repeat application for thick buildup areas.
- Do not use on energized equipment.

VIII. Package Description

Part Number	Container Size
03017	16 oz Aerosol

IX. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

X. Special Use Warnings

Aerosol Cans

Do not puncture, incinerate or store above 120° F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

PRODUCT WARRANTY: CRC offers a conditional warranty on this product for the period of 2 years from the date of manufacture.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.

CRC Industries, Inc.
Technical Service: (800)521-3168

Industrial Products Division
Customer Service: (800)272-4620

Warminster, PA 18974
CRC On-Line: (215)442-6260