Connectors



Häfele Rafix Installer Kit

ixconnect

- > For quick, accurate drilling of Rafix 20, Rafix-SE 32 and Rafix 20 Flush systems
- > Can also be used to drill 5 mm system holes in side panels

→ Drillbit Ø10 mm, optional

> For Rafix SE-32

We reserve the right to alter specifications without notice.

Dimensions in mm, inches are approximate.

Dimensional data not binding.

- > 10 mm x 139 mm, RH
- > Material: Carbide

Item No.
001.24.319

ightarrow Drillbit Ø5 mm Hex, optional



Item No.
001.20.508

ightarrow Drillbit Ø20 mm Countersunk, optional

- > For Rafix 20 Flush
- > 20 mm x 139 mm, RH
- > Material: Carbide

Item No.
001.24.426

z. For Rafix 20 drill Ø20 mm hole with 001.28.750 depth gauge with drill bit Ø20 mm 1. Align the jig with either shelf bottom panel side (front, back)

Rafix 20

(13/16")

9.5

(3/8")

10

(17/16")

11

Connectors and Shelf Supports

HAFELE

Item No.


Häfele Rafix Installer Kit

ixconnect


- > For quick, accurate drilling of Rafix 20 and Rafix 20 Flush systems
- > Can also be used to drill 5 mm system holes in side panels

→ Kit with System Holes





	001.25.638
Supplied With	Item No.
Rafix drill guide with system holes	001.25.631
Rafix depth gauge	001.28.750
Drillbit Ø20 x 139 RH	001.24.425
Stop ring Ø10 shank	001.42.693



ightarrow Drillbit Ø5 mm Hex, optional



Item No.
001.20.505

→ Drillbit Ø20 mm Countersunk, optional

- > For Rafix 20 Flush
- > 20 mm x 139 mm, RH
- > Material: Carbide

Item No.
001 24 426

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to atter specifications without notice.

11

Connectors and Shelf Supports

HAFELE

Specialty Bits

→ Vix Bit



- > Self-centering
- > Adjustable for depth > Material: Steel

For use with	Item No.
#2, #3 and #4 screws 5/64" bit	001.42.061
#5 and #6 screws 7/64" bit	001.42.030
#14 screws 13/64" bit	001.42.020
#8, #9 and #10 screws 9/64" bit	001.42.060

→ Forstner Style Drill Bit



> Length: 139 mm > Material: Carbide

Description	Item No.
*10 (25/64")	001.24.319
*12 (15/32")	001.24.489
*15 (19/32")	001.24.443
*20 (25/32")	001.24.425
*20 (25/32") countersunk	001 24 426

Note

*Can be used with red jig on page 11.29.

→ Wave Cutter Drill Bit



Description	Item No.
20 (25/32")	001.04.156
35 (1 3/8")	001.04.157

12

Consumables and Tools



ightarrow Twist Drill Bit for Depth Gauge 15



> Length: 130 mm x 8 mm shank

Ø	Item No.
5 (3/16")	001.06.683
8 (5/16")	001.06.686
10 (25/64")	001.06.687

ightarrow Forstner Drill Bit for Depth Gauge 32 and 48



> Length: 139 mm x 10 mm shank

Ø	Item No.
12 (15/32")	001.24.489
15 (19/32")	001.24.443
20 (25/32")	001.24.425
20 (25/32") countersunk	001.24.426
35 (1 3/8")	001.24.351

→ Brad Point Drill Bit for Minifix Bolt



> 1/4" hex shank

Ø	Item No.
8 (5/16")	001.20.508