

Drill Bits

→ Brad Point Drill Bit



> Material: High-speed Steel

Ø x L	Item No.
10 x 254 (3/8" x 10")	001.85.480
10 x 305 (3/8" x 12")	001.85.481
10 x 356 (3/8" x 14")	001.85.482
8 x 254 (5/16" x 10")	001.85.430
8 x 305 (5/16" x 12")	001.85.431
8 x 406 (5/16" x 16")	001.85.432
8 x 457 (5/16" x 18")	001.85.433

→ Brad Point Twist Drill Bit



> Material: High-speed Steel

Ø	Item No.
5 (13/64")	001.20.518
7.5 (19/64")	001.20.061
8 (5/16")	001.20.123
10 (25/64")	001.20.519
12 (15/32")	001.20.169
15 (19/32")	001.20.540
20 (25/32")	001.20.541

→ Twist Drill Bit



> Material: High-speed Steel

Ø x L	Length	Item No.
3.2 (1/8")	9 cm	001.41.079
5 (13/64")	9 cm	001.41.168
7 (9/32")	10.5 cm	001.41.220
8 (5/16")	11.5 cm	001.41.248
10 (25/64")	13 cm	001.41.293
15 (19/32")	16.2 cm	001.06.034
20 (25/32")	20.5 cm	001.06.061

→ Brad Point Drill Bit



> 6 mm (1/4") hex shank
> Material: High-speed Steel

Ø	Item No.
3 (1/8")	001.20.503
4 (5/32")	001.20.504
5 (3/16")	001.20.505
6 (1/4")	001.20.506
8 (5/16")	001.20.508
9 (23/64")	001.20.509
10 (25/64")	001.20.510
12 (15/32")	001.20.512
13 (33/64")	001.20.513
14 (35/64")	001.20.514

→ Brad Point Twist Drill Bit



Description	Item No.
Carbide 5 (13/64") L 85 (3 3/8")	001.20.098
*Carbide 5 (13/64") with collar L 104.5 (4 1/8")	001.24.498
HSS 10 (25/64") w/stop ring	006.47.012
Carbide 10 (25/64") w/stop ring	006.47.076

Note

*Can be used with red jig on page 11.29.

→ Special Bit



> For press-fit connector
> Length: 63 mm (2 1/2")

Version	Item No.
HSS	006.47.012
HM-tipped	006.47.076