

Extension Cords

→ Contractor Grade Extension Cord



- > Primelight® indicator light shows when power is on
- > Oversized plugs & strain reliefs prevent wire from separating from the plugs
- > Brass, nickel-coated blade resists corrosion & arcing
- > Water resistant
- > Flame retardant
- > Flexible in temperatures from -40° – +140° F
- > 15A/125V/1875W
- > cULus or equivalent certified
- > Color: yellow

L x W x H x D	Item No.
7.6 m x 229 mm x 394 mm x 76 mm (25' x 6 1/4" x 13" x 2")	008.74.200
15.2 m x 159 mm x 330 mm x 51 mm (50' x 6 1/4" x 13" x 2")	008.74.201
30.5 m x 159 mm x 330 mm x 51 mm (100' x 9" x 15 1/2" x 3")	008.74.202

→ Bulldog Tough Extension Cord



- > Primelight® indicator light shows when power is on
- > If the light fails, it will not affect the operation of the extension cord
- > Brass, nickel-coated blade resists corrosion
- > Flexible in temperatures from -58° – +221° F
- > Water, oil and abrasion resistant; Flame retardant
- > Ultra Flexible; Lifetime warranty
- > 15A/125V/1875W; cULus or equivalent certified
- > Color: yellow

L x W x H x D	Item No.
7.6 m x 133 mm x 330 mm x 51 mm (25' x 6 1/4" x 13" x 2")	008.74.203
15.2 m x 190.5 mm x 381 mm x 63.5 mm (50' x 7 1/2" x 15" x 2 1/2")	008.74.204
30.5 m x 159 mm x 394 mm x 76 mm (100' x 9" x 15 1/2" x 3")	008.74.205

→ Neon Flex Extension Cord



- > Water resistant
- > Flame retardant
- > Abrasion resistant
- > Brass, nickel-coated blade resists corrosion
- > Flexible temperature range (-58F – +221F)
- > Primelight® indicator light
- > 15A/125V/1875W
- > cULus or equivalent certified
- > Color: Hi-vis pink

L x W x H x D	Item No.
15.2 m x 190.5 mm x 381 mm x 63.5 mm (50' x 7 1/2" x 15" x 2 1/2")	008.74.206
30.5 m x 159 mm x 394 mm x 76 mm (100' x 9" x 15 1/2" x 3")	008.74.207

→ Jobsite Locking Extension Cord



- > Water resistant
- > Flame retardant
- > Flexible in temperatures from -40°F – +140°F
- > Abrasion resistant
- > Brass, nickel-coated blade resists corrosion
- > Primelight® indicator light
- > Primelok® locking connector
- > 15A/125V/1875W
- > cULus or equivalent certified
- > Color: red/blue

L x W x H x D	Item No.
7.6 m x 133 mm x 330 mm x 51 mm (25' x 6 1/4" x 13" x 2")	008.74.208
15.2 m x 190.5 mm x 381 mm x 63.5 mm (50' x 7 1/2" x 15" x 2 1/2")	008.74.209
30.5 m x 159 mm x 394 mm x 76 mm (100' x 9" x 15 1/2" x 3")	008.74.210

→ Worklight



- > Long-life, energy efficient LEDs are cool to the touch
- > Sealed on/off power switch prevents dust & debris from entering the work light
- > Versatile design extends to 292 mm (11 1/2") for floodlight & collapses to 159 mm (7 1/2") for flashlight use
- > 2 Hands-free options: Hanging Hook
Magnetic base grips steel surfaces & swivels to direct light where it's needed
- > L x W x H: 159–292 x 170 x 63.5 mm
(7 1/2"–11 1/2" x 6 11/16" x 2 1/2")
- > Color: red/black

Color	Item No.
red/black	008.74.211
Supplied with 3 AA Batteries	