


SAFE-O-MAT® 800 Series - Coin Return

Overlay Installation Ø22 (Ø7/8") 8 (5/16") (5/8")O = Overlay



> For use on wood, laminate and plastic lockers

Areas of Application

> Fitness Centers, Amusement Parks, Resorts, Transportation Terminals

To Lock

- 1. Insert coin(s) into slot
- 2. Close door, turn key to extend bolt, coin(s) is temporarily retained
- 3. Remove key

To Unlock

Insert and turn key to retract bolt, coin is returned to Coin(s) Return Catch.

Technical Data


 $L \times H \times W$: 110 x 119 x 57.5 mm (4 5/16" × 4 11/16" × 2 1/4")

Weight: 225 g (8 oz.) 0°-60°C (32°-140°F) Temperature: Humidity: 10%-95% (non-condensing)

Currency: 1 quarter, US, token

→ Coin Return Lock





> Door thickness: 13-26 mm (1/2"-1") > Cabinet width: min. 140 mm (5 1/2")

> Material: Plastic; Color: gray

Handing	Coin	Item No.
Left	1 quarter	231.53.810
Right	1 quarter	231.53.811
Right	1 token	231.53.817

Supplied With

4 Mounting screws

Outside instruction decal

Note

Screw length depends on door thickness.

Other currency or token locks available upon request.

Please contact Häfele at 1-800-423-3531 and have the

following information available:

"Handing" specifications

Key Plan specifications

Every Order requires:

Cylinder change (removal) key, and 1 master key, sold separately

For all applicable Mounting/Programming Instructions and Specifications please visit www.hafele.com.For all applicable Mounting/Programming

Instructions and Specifications please visit www.hafele.com.

Key and Core

Handing	Series	Item No.
Right	1	231.53.511
Right	2	231.53.512
Right	3	231.53.513
Left	1	231.53.611
Left	2	231.53.612
Left	3	231.53.613

Each Lock requires:

Cylinder core and user key, sold separately

Other key series available upon request.

Accessor	es	page 10.70

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to atter specifications without notice.

FC 10.66

10