
HAFELE

Dowels

→ Wood Dowels (Fluted)






- > Fluted dowels allow the glue to distribute evenly over the entire surface
- > Suitable for non-glued applications in combination with mechanical fasteners
- > Application:
 - Glued case connections
 - Non-glued connections in combination with mechanical fastener
- > Material: Kiln-dried hardwood

mm				
AxB	Item No.	Packing	Item No.	Bulk
5 x 30	267.83.030	1,000	267.83.032	52,000
5 x 35	267.83.035	1,000	267.83.036	46,000
5 x 40	267.83.040	1,000	267.83.042	30,000
6 x 25	267.83.125	1,000	267.83.127	44,000
6 x 30	267.83.130	1,000	267.83.132	35,400
8 x 25	267.83.225	1,000	267.83.227	23,000
8 x 30	267.83.230	1,000	267.83.233	19,200
8 x 32	267.83.232	1,000	267.83.234	17,800
8 x 35	267.83.235	1,000	267.83.237	16,400
8 x 38	267.83.238	1,000	267.83.239	15,000
8 x 40	267.83.240	1,000	267.83.242	14,200
8 x 50	267.83.250	1,000	267.83.252	12,000
10 x 30	267.83.330	1,000	267.83.332	25,000
10 x 50	-	-	267.83.350	13,000

Inch				
AxB	Item No.	Packing	Item No.	Bulk
1/4" x 1"	267.80.102	1,000	267.80.103	38,700
1/4" x 1 1/4"	267.80.105	1,000	267.80.106	29,600
1/4" x 1 1/2"	-	-	267.80.107	24,000
5/16" x 1"	-	-	267.80.202	10,000
5/16" x 1 1/4"	267.80.205	1,000	267.80.206	17,800
5/16" x 1 1/2"	267.80.207	1,000	267.80.208	15,000
3/8" x 1 1/2"	267.80.307	1,000	267.80.308	13,000
3/8" x 2"	267.80.312	1,000	267.80.313	13,000
1/2" x 3"	267.80.719	1,000	267.80.720	5,000

ightarrow Pre-Glued Multi-Grooved (Fluted) Wood Dowel



- > 100% glue coverage creates superior holding strength
- > Eliminates clean up time on your product during and after assembly
- > Material: Kiln-dried hardwood

mm				
AxB	Item No.	Packing	Item No.	Bulk
6 x 25	267.84.125	1,000	267.84.126	44,000
6 x 30	267.84.130	1,000	267.84.131	35,000
8 x 25	267.84.225	1,000	267.84.226	23,000
8 x 30	267.84.230	1,000	267.84.231	20,000
8 x 32	267.84.232	1,000	267.84.233	20,000
8 x 35	267.84.235	1,000	267.84.236	20,000
8 x 38	267.84.238	1,000	267.84.239	15,000

Inch/mm		
AxB	Item No.	Bulk
5/16" x 35	267.84.237	20,000

Note


How to use a Pre-glued dowel:

- > Simply replace your glue with water
- > Fill approximately $1/\bar{3}$ of the hole with water and insert dowel
- > A spray mist bottle can also be used by holding the nozzle next to the hole, and spraying 1 or 2 times before you insert the dowel

ightarrow EXACT Dowel







- > For solid and detachable connections
- > Made of high grade, high-impact plastic for invisible and corrosion proof connections
- > The tooth-like grooves of the dowels guarantee a tight fit even without glue
- > EXACT dowels save labor on ceiling, door and wall paneling as they can also be driven into brick and concrete
- > Material: Plastic

Color	Item No.
white	267.70.700

Connectors and Shelf Supports

11

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.