



Salice Pacta



- > With automatic closing spring or Push version
- > Integrated soft opening mechanism in opening direction
- > Without additional hinge connection
- > Flap and base panel are on one level in open position
- > Clips onto cabinet
- > Drilling depth: 13 mm (1/2")
- > Adjustment facility: Side adjustment from -1.5 – +1.5 mm (-1/16" – +1/16")
- Height adjustment from -1.5 – +1.5 mm (-1/16" – +1/16")
- Depth adjustment from -0.5 – +2.8 mm (-1/64" – +1/8")
- > Overlay: 17 mm (11/16") (fixed)
- > Door height: 280–400 mm (11 1/32"–15 3/4")
- > Door width: <900 mm (35 7/16")
- > Material: Zinc Alloy; Finish: nickel-plated

Note Cover caps, see page 9.164

→ Flap Stay




Weight capacity table

Door height	Door weight in lbs.		
	Model W	Model I	Model S
280 (11 1/32")	6.2-9.5	9.5-14.5	14.7-21
300 (11 13/16")	5.7-9	9-13.6	13.6-9.7
320 (12 5/8")	5.5-8.6	8.4-12.8	12.8-18.3
340 (13 3/8")	5.1-8.2	8.2-11.9	11.9-17.4
360 (14 3/16")	4.8-7.7	7.9-11	11-16.3
380 (14 15/16")	4.6-7.3	7.7-10.3	10.3-15.4
400 (15 3/4")	4.4-5.3	7.3-9.9	9.9-14.5

Model	With automatic closing spring	Push, without automatic closing spring
W	365.13.700	365.13.710
I	365.13.701	365.13.711
S	365.13.702	365.13.712

Supplied With 2 Hinges, 2 Mounting plates, 2 Soft opening mechanisms, Screws

Note Order Push magnetic catch separately



① Side panel ② Safety lock screw D = overlay

Door thickness	16 (5/8")	17 (1 1/16")	18 (23/32")	19 (3/4")	20 (25/32")	21 (27/32")	22 (7/8")	23 (29/32")	24 (15/16")	25 (1")	26 (1 1/32")	27 (1 1/16")	28 (1 3/32")
Distance to cup E (fixed) 4.5 mm (11/64")	1.3 (3/64")	2.1 (15/64")	3.0 (1/8")	3.9 (5/32")	4.8 (3/16")	5.7 (7/32")	6.6 (17/64")	7.5 (19/64")	8.5 (21/64")	9.4 (3/8")	10.4 (13/32")	11.3 (7/16")	12.3 (31/64")
Minimum gap F													

→ Center Hinge



Finish	Item No.
gray	372.76.600
white	372.76.601
black	372.76.602